

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)
[170-03058](#)

For any questions, you can email us directly:
sales@integrated-circuit.com

HellermannTyton

170-03058



Article Number: 170-03058

Resin Coated Fiberglass Sleeve, 0.25" Dia., Black, 50.0 ft/Standard Reel



Download drawing



Download spec sheet

Base Data

Local Order Number 170-03058

Type BSHTFG140

Color Black (BK)

- Features and Benefits**
- An extremely tough sleeving material which provides thermal protection up to 1,200°F.
 - Sturdy construction maintains its tight structure under extreme shaking, scraping, pressure and varying temperature conditions.
 - Cuts easily with ordinary scissors for easy application.
 - UL VW-1 flammability rating for use in conditions requiring a very high degree of flame resistance.

Product Description An extremely high-temperature resistant sleeving designed to protect wires and cables subjected to continuous temperature variations, vibration, abrasion, and mechanical stress.

Short Description Resin Coated Fiberglass Sleeve, 0.25" Dia., Black, 50.0 ft/Standard Reel

Product Dimensions

Length L (Imperial) 50.0 ft

Length L (Metric) 15.2 m

Reel Length (imperial) 50.0 ft

Bundle Diameter Max. (Imperial) 0.375 "

Bundle Diameter Max. (Metric) 9.5 mm

Nominal Diameter (Imperial) 1/4 "

Nominal Diameter (Metric) 6.4 mm

Logistics and Packaging

Package Quantity 50 ft

Weight (Metric) 0.45 kg

Weight (imperial) 1.0 lbs

Material and Specifications

Material Glass Fiber (GF)

Operating Temperature -94°F to +1202°F (-70°C to +650°C)

ROHS Compliant Yes

UL Recognized (US) Yes



Distributor of HellermannTyton: Excellent Integrated System Limited

Datasheet of 170-03058 - 1/4" RESIN FIBERGLASS SLEEVING

Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com
