



**Distributor of HellermannTyton: Excellent Integrated System Limited**

Datasheet of 170-03063 - 3/4" ALUM FIBERGLASS SLVNG

Contact us: [sales@integrated-circuit.com](mailto:sales@integrated-circuit.com) Website: [www.integrated-circuit.com](http://www.integrated-circuit.com)

---

## **Excellent Integrated System Limited**

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)

[170-03063](#)

For any questions, you can email us directly:

[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)

# HellermannTyton

170-03063



Article Number: 170-03063

Aluminum Laminated Fiberglass Sleeving Tube, 0.75" Dia., Silver 100.0 ft/Standard Reel



Download drawing



Download spec sheet



Download tech sheet

## Base Data

Local Order Number 170-03063

Type BSHTTST34SR

Color Silver (SR)

- Features and Benefits**
- A layer of aluminum provides protection from chemicals, scraping, cuts and abrasion.
  - Additional layer also provides insulation barrier for vulnerable wires and cables within high temperature environments.
  - Cuts with ordinary scissors for fast, easy application.

**Product Description** A tubular shaped sleeving product that combines the protection of bonded aluminum and fiberglass into a single solution that is able to deflect radiant heat away from sensitive components inside the tube.

**Short Description** Aluminum Laminated Fiberglass Sleeving Tube, 0.75" Dia., Silver 100.0 ft/Standard Reel

## Product Dimensions

Length L (Imperial) 100.0 ft

Length L (Metric) 30.48 m

Reel Length (imperial) 100.0 ft

Bundle Diameter Max. (Imperial) 0.687 "

Bundle Diameter Max. (Metric) 17.5 mm

Nominal Diameter (Imperial) 3/4 "

Nominal Diameter (Metric) 19.1 mm

## Logistics and Packaging

Package Quantity 100 ft

Package Quantity (Metric) 1 Reel

Weight (Metric) 1.57 kg

Weight (imperial) 3.45 lbs

## Material and Specifications

**Material** Aluminium (AL)  
Glass Fiber (GF)

**Flammability** non flammable

**Operating Temperature** -76°F to +491°F (-60°C to +255°C)

**ROHS Compliant** Yes



**Distributor of HellermannTyton: Excellent Integrated System Limited**

Datasheet of 170-03063 - 3/4" ALUM FIBERGLASS SLVNG

Contact us: [sales@integrated-circuit.com](mailto:sales@integrated-circuit.com) Website: [www.integrated-circuit.com](http://www.integrated-circuit.com)

---