

## **Excellent Integrated System Limited**

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)  
[170-03076](#)

For any questions, you can email us directly:

[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)

# HellermannTyton

170-03076



**Article Number:** 170-03076

**Expandable Braided Sleeveing, 0.25" Dia., Orange, 1000.0 ft/Bulk Reel**



Download drawing



Download spec sheet

## Base Data

**Local Order Number** 170-03076

**Type** BSP143B

**Color** Orange (OG)

- Features and Benefits**
- Weave construction adjusts to twisting and flexing without creating wrinkles or bends.
  - Durable construction offers excellent abrasion and cut-through resistance as well as inertness to most chemicals and fungus.
  - Color options available to provide easy visual and safety identification of critical wiring components.
  - Expands to 150% of nominal diameter for fast, easy installation.

**Product Description** General purpose expandable braided sleeveing provides flexible abrasion protection for wire bundles and hoses.

**Short Description** Expandable Braided Sleeveing, 0.25" Dia., Orange, 1000.0 ft/Bulk Reel

## Product Dimensions

**Length L (Imperial)** 1000.0 ft

**Length L (Metric)** 304.8 m

**Reel Length (imperial)** 1000.0 ft

**Bundle Diameter Min. (Imperial)** 0.125 "

**Bundle Diameter Min. (Metric)** 3.2 mm

**Bundle Diameter Max. (Imperial)** 0.437 "

**Bundle Diameter Max. (Metric)** 11.1 mm

**Nominal Diameter (Imperial)** 1/4 "

**Nominal Diameter (Metric)** 6.4 mm

## Logistics and Packaging

**Quantity Per** reel

**Package Quantity** 1000 ft

**Package Quantity (Metric)** 1000.0 ft

**Weight (Metric)** 1.18 kg

**Weight (imperial)** 2.6

## Material and Specifications

**Material** Polyester (PET)

**Material Shortcut** PET

**Flammability** UL94 V0  
FAR 25



**Distributor of HellermannTyton: Excellent Integrated System Limited**

Datasheet of 170-03076 - 1/4" PET BRAIDED SLEEVING

Contact us: [sales@integrated-circuit.com](mailto:sales@integrated-circuit.com) Website: [www.integrated-circuit.com](http://www.integrated-circuit.com)

---

**Halogenfree** Yes

**Operating Temperature** -94°F to +257°F (-70°C to +125°C)

**ROHS Compliant** Yes

**UL Listed (US and Canada)** Yes

**UL Recognized (US and Canada)** Yes