

## Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)  
[170-03079](#)

For any questions, you can email us directly:  
[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)

# HellermannTyton

170-03079



Article Number: 170-03079

Expandable Braided Sleeveing, 1.0" Dia., Orange, 250.0 ft/Bulk Reel



Download drawing



Download spec sheet

## Base Data

Local Order Number 170-03079

Type BSP103B

Color Orange (OG)

- Features and Benefits**
- Weave construction adjusts to twisting and flexing without creating wrinkles or bends.
  - Durable construction offers excellent abrasion and cut-through resistance as well as inertness to most chemicals and fungus.
  - Color options available to provide easy visual and safety identification of critical wiring components.
  - Expands to 150% of nominal diameter for fast, easy installation.

**Product Description** General purpose expandable braided sleeveing provides flexible abrasion protection for wire bundles and hoses.

**Short Description** Expandable Braided Sleeveing, 1.0" Dia., Orange, 250.0 ft/Bulk Reel

## Product Dimensions

Length L (Imperial) 250.0 ft

Length L (Metric) 76.2 m

Reel Length (imperial) 250.0 ft

Bundle Diameter Min. (Imperial) 0.625 "

Bundle Diameter Min. (Metric) 15.9 mm

Bundle Diameter Max. (Imperial) 1.625 "

Bundle Diameter Max. (Metric) 41.3 mm

Nominal Diameter (Imperial) 1 "

Nominal Diameter (Metric) 25.4 mm

## Logistics and Packaging

Quantity Per reel

Package Quantity 250 ft

Package Quantity (Metric) 250.0 ft

Weight (imperial) 3.35

Weight (Metric) 1.52 kg

## Material and Specifications

Material Polyester (PET)

Material Shortcut PET

Flammability UL94 V0  
FAR 25



**Distributor of HellermannTyton: Excellent Integrated System Limited**

Datasheet of 170-03079 - 1" PET BRAIDED SLEEVING

Contact us: [sales@integrated-circuit.com](mailto:sales@integrated-circuit.com) Website: [www.integrated-circuit.com](http://www.integrated-circuit.com)

---

**Halogenfree** Yes

**Operating Temperature** -94°F to +257°F (-70°C to +125°C)

**ROHS Compliant** Yes

**UL Recognized (US and Canada)** Yes