

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)
[170-03090](#)

For any questions, you can email us directly:
sales@integrated-circuit.com

HellermannTyton

170-03090



Article Number: 170-03090

Flame Retardant Expandable Braided Sleeveing, 0.25" Dia., Black, 1000.0 ft/Bulk Reel



Download drawing



Download spec sheet

Base Data

Local Order Number 170-03090

Type BSPFR140B

Color Black (BK)

Features and Benefits

- Treated polyester material contains a combustion inhibitor for use in applications where flame retardancy is required.
- Braided design allows sleeveing to expand by 150% to accommodate variations in wire bundle and eases installation.

Product Description A flame retardant woven (threaded) polyester sleeveing that is resistant to cuts and abrasion, and contains a combustion inhibitor allowing it to achieve a UL and CSA flame resistance rating of VW-1. Contains white tracer thread for easy identification.

Short Description Flame Retardant Expandable Braided Sleeveing, 0.25" Dia., Black, 1000.0 ft/Bulk Reel

Product Dimensions

Length L (Imperial) 1000.0 ft

Length L (Metric) 304.8 m

Reel Length (imperial) 1000.0 ft

Bundle Diameter Min. (Imperial) 0.125 "

Bundle Diameter Min. (Metric) 3.2 mm

Bundle Diameter Max. (Imperial) 0.437 "

Bundle Diameter Max. (Metric) 11.1 mm

Nominal Diameter (Imperial) 1/4 "

Nominal Diameter (Metric) 6.4 mm

Logistics and Packaging

Quantity Per reel

Package Quantity 1000 ft

Package Quantity (Metric) 1000.0 ft

Weight (Metric) 1.1 kg

Weight (imperial) 2.4 lbs

Material and Specifications

Material Polyester (PET)

Material Shortcut PET

Flammability FMVSS 302



VW-1
FAR 25

Operating Temperature -94°F to +257°F (-70°C to +125°C)

ROHS Compliant Yes

Certification/Specification UL94

UL Recognized (US and Canada) Yes