



Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)
[170-03109](#)

For any questions, you can email us directly:
sales@integrated-circuit.com

HellermannTyton

170-03109



Article Number: 170-03109

Plenum Rated Expandable Braided Sleeveing (Halar), 1.0" Dia., White, 65.0 ft/Reel



Download drawing



Download spec sheet

Base Data

Local Order Number 170-03109

Type BSHLR1010

Color White (WH)

Features and Benefits

- Meets UL 2024 and NFPA 262 specifications meets requirements for use in plenum applications.
- Technically advanced monofilament material is rated as low smoke, flame resistant and can withstand exposure to Cobal 60 radiation.
- Exceeds requirements of FMVSS 302 as well as aviation industry requirements of FAR25.

Product Description Halar self-extinguishing sleeveing is used where flammability, high temperature endurance and low outgassing are the primary concern.

Short Description Plenum Rated Expandable Braided Sleeveing (Halar), 1.0" Dia., White, 65.0 ft/Reel

Product Dimensions

Length L (Imperial) 65.0 ft

Length L (Metric) 19.8 m

Reel Length (imperial) 65.0 ft

Bundle Diameter Min. (Imperial) 0.63 "

Bundle Diameter Min. (Metric) 16.0 mm

Bundle Diameter Max. (Imperial) 1.63 "

Bundle Diameter Max. (Metric) 41.3 mm

Nominal Diameter (Imperial) 1 "

Nominal Diameter (Metric) 25.4 mm

Logistics and Packaging

Quantity Per reel

Package Quantity 65 ft

Weight (Metric) 0.65 kg

Weight (imperial) 1.43 lbs

Material and Specifications

Material Polyamide 6.6 (E/CTFE)

Material Shortcut E/TFE

Flammability UL VW-1
FAR 25

Operating Temperature -103°F to +302°F (-75°C to +150°C)



Distributor of HellermannTyton: Excellent Integrated System Limited

Datasheet of 170-03109 - 1" PLENUM RATED SLEEVING

Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

ROHS Compliant Yes

Certification/Specification UL2024

UL Recognized (US and Canada) Yes