



Distributor of HellermannTyton: Excellent Integrated System Limited

Datasheet of 170-03115 - 2" PLENUM RATED SLEEVING

Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)

[170-03115](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

HellermannTyton

170-03115



Article Number: 170-03115

Plenum Rated Expandable Braided Sleeveing (Halar), 2.0" Dia., White, 50.0 ft/Reels



Download drawing



Download spec sheet

Base Data

Local Order Number 170-03115

Type BSHLR2010

Color White (WH)

- Features and Benefits**
- Meets UL 2024 and NFPA 262 specifications meets requirements for use in plenum applications.
 - Technically advanced monofilament material is rated as low smoke, flame resistant and can withstand exposure to Cobal 60 radiation.
 - Exceeds requirements of FMVSS 302 as well as aviation industry requirements of FAR25.

Product Description Halar self-extinguishing sleeveing is used where flammability, high temperature endurance and low outgassing are the primary concern.

Short Description Plenum Rated Expandable Braided Sleeveing (Halar), 2.0" Dia., White, 50.0 ft/Reels

Product Dimensions

Length L (Imperial) 50.0 ft

Length L (Metric) 15.2 m

Reel Length (imperial) 50.0 ft

Bundle Diameter Min. (Imperial) 1.5 "

Bundle Diameter Min. (Metric) 38.1 mm

Bundle Diameter Max. (Imperial) 3.5 "

Bundle Diameter Max. (Metric) 88.9 mm

Nominal Diameter (Imperial) 2 "

Nominal Diameter (Metric) 50.8 mm

Logistics and Packaging

Quantity Per reel

Package Quantity 50 ft

Weight (imperial) 2.3 lbs

Weight (Metric) 1.04 kg


Material and Specifications

Material Polyamide 6.6 (E/CTFE)

Material Shortcut E/TFE

Flammability UL VW-1
FAR 25

Operating Temperature -103°F to +302°F (-75°C to +150°C)



Distributor of HellermannTyton: Excellent Integrated System Limited

Datasheet of 170-03115 - 2" PLENUM RATED SLEEVING

Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

ROHS Compliant Yes

Certification/Specification UL2024

UL Recognized (US and Canada) Yes