

## Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)

[170-03117](#)

For any questions, you can email us directly:

[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)

# HellermannTyton

170-03117



**Article Number: 170-03117**

**Fray Resistant Flame Retardant Expandable Braided Sleeveing, 0.25" Dia., Black, 1000.0 ft/Bulk Reel**



Download drawing



Download spec sheet

## Base Data

**Local Order Number** 170-03117

**Type** BSSCFR140B

**Color** Black (BK)

**Features and Benefits**

- Increased braid density coverage provides higher level of abrasion resistance without losing flexibility.
- Treated yarns extinguish quickly and reduces potential flame spread to surrounding components.
- Cuts with ordinary scissors without fraying ends.

**Product Description** Treated polyester yarns that can be cut with sharp scissors and provides flame retardant properties. Well suited for situations where access to a hot knife is either impractical or impossible. Contains white tracer thread for easy identification.

**Short Description** Fray Resistant Flame Retardant Expandable Braided Sleeveing, 0.25" Dia., Black, 1000.0 ft/Bulk Reel

## Product Dimensions

**Length L (Imperial)** 1000.0 ft

**Length L (Metric)** 304.8 m

**Reel Length (imperial)** 1000.0 ft

**Bundle Diameter Min. (Imperial)** 0.156 "

**Bundle Diameter Min. (Metric)** 4.0 mm

**Bundle Diameter Max. (Imperial)** 0.437 "

**Bundle Diameter Max. (Metric)** 11.1 mm

**Nominal Diameter (Imperial)** 1/4 "

**Nominal Diameter (Metric)** 6.4 mm

## Logistics and Packaging

**Quantity Per** reel

**Package Quantity** 1000 ft

**Package Quantity (Metric)** 1000.0 ft

**Weight (imperial)** 4.6 lbs

**Weight (Metric)** 2.1 kg

## Material and Specifications

**Material** Polyester (PET)

**Material Shortcut** PET

**Flammability** Mil-202  
UL VW-1



**Distributor of HellermannTyton: Excellent Integrated System Limited**

Datasheet of 170-03117 - 1/4" FRAY RESIS FR BRDD SLVNG

Contact us: [sales@integrated-circuit.com](mailto:sales@integrated-circuit.com) Website: [www.integrated-circuit.com](http://www.integrated-circuit.com)

---

**Operating Temperature** -94°F to +257°F (-70°C to +125°C)

**ROHS Compliant** Yes

**UL Recognized (US and Canada)** Yes