

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:


[HellermannTyton](#)
[173-60600](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

HellermannTyton

173-60600



Article Number: 173-60600

Electromagnetic Protection Sleeve, Flame Retardant, 6 mm Dia., Tin Plated Copper+Polyester, 100 m/reel



Download spec sheet

Base Data

Local Order Number 173-60600

Type HEGMIPV006

Color Tin-coloured and Black (TCBK)

Features and Benefits The patented material mix of the HEGMIPV0 braided sleeving offer electromagnetic protection and secure cable bundling.

The special combination of tin-plated copper and polyester yarn offers optimal inside and outside abrasion resistance. In contrast to purely copper braids, HEGMIPV0 is easy to apply without any threads and breaks in the metal, even if there is restricted space. As a result Helagain HEGMIPV0 is particularly suitable for applications with movement and little space. The sleeve fulfils the requirements of the international EMI norm CISPR25 (10 KHz to 1 GHz).

HEGMIPV0 is self-extinguished according to UL94 V0 and it is particularly suitable for areas, wherever fire protection is important.

HEGMIPV0 will be delivered with an inner tube to make insertion of cables easier and protects the sleeve from deformation during transport.

Product Description The patented material mix of the HEGMIPV0 braided sleeving offer electromagnetic protection and secure cable bundling.

The special combination of tin-plated copper and polyester yarn offers optimal inside and outside abrasion resistance. In contrast to purely copper braids, HEGMIPV0 is easy to apply without any threads and breaks in the metal, even if there is restricted space. As a result Helagain HEGMIPV0 is particularly suitable for applications with movement and little space. The sleeve fulfils the requirements of the international EMI norm CISPR25 (10 KHz to 1 GHz).

HEGMIPV0 is self-extinguished according to UL94 V0 and it is particularly suitable for areas, wherever fire protection is important.

HEGMIPV0 will be delivered with an inner tube to make insertion of cables easier and protects the sleeve from deformation during transport.

Short Description Electromagnetic Protection Sleeve, Flame Retardant, 6 mm Dia., Tin Plated Copper+Polyester, 100 m/reel

Product Dimensions

Length L (Imperial) 328.0 ft

Length L (Metric) 100.0 m

Reel Length (imperial) 328.0 ft

Bundle Diameter Min. (Imperial) 0.2 "

Bundle Diameter Min. (Metric) 5 mm

Bundle Diameter Max. (Imperial) 0.4 "

Bundle Diameter Max. (Metric) 10 mm

Diameter D (imperial) 0.24 "

Diameter D (metric) 6 mm

Nominal Diameter (Imperial) 1/4 "

Nominal Diameter (Metric) 6 mm

Logistics and Packaging

Quantity Per metre

Package Quantity (Metric) 100 m

Carton Quantity 100

Weight (imperial) 6.28

Weight (Metric) 28.5 g/M

Material and Specifications

Material Tin-plated copper (TNCU)
Polyester (PBT)

Material Shortcut TNCU
PBT

Flammability UL94 V0
FMVSS 302

Halogenfree No

Operating Temperature -40°F to +347°F (-40°C to +175°C)

ROHS Compliant Yes