

## **Excellent Integrated System Limited**

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)

[181-00249](#)

For any questions, you can email us directly:

[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)

# HellermannTyton

## 181-00249

**Article Number: 181-00249****Solid Wall Wiring Duct, 2" X 5", Non-Adhesive, PVC, White, 30ft/Box**[Download drawing](#)[Download spec sheet](#)

### Base Data

**Local Order Number** 181-00249**Type** SD2X5**Color** White (WH)**Features and Benefits**

- A temporary film is applied to the covers to protect against scratches and is writable for identification during installation.
- Cover is flush with the side of the duct for increased wire capacity and allows for tight, side by side duct placement.
- Covers are provided with a non-slip lining, which insures the covers remain in place during vibration, yet they easily snap on and off. (Covers to be purchased separately)

**Product Description** HellermannTyton's Pro-Duct, Solid Wall wiring duct efficiently routes and protects wire and cable. Solid Wall wiring duct is designed for straight wire runs where break outs are not required. Pro-Duct, Solid Wall wiring duct is manufactured from high impact, rigid PVC, comes in standard colors of white, gray and black, and is available in 6 foot lengths.**Short Description** Solid Wall Wiring Duct, 2" X 5", Non-Adhesive, PVC, White, 30ft/Box

### Product Dimensions

**Length L (Imperial)** 6.0 ft**Length L (Metric)** 1.83 m**Width W (Imperial)** 2.0 "**Width W (Metric)** 50.8 mm**Width W2 (Imperial)** 2.0 "**Width W2 (Metric)** 50.8 mm**Width W6 (Imperial)** 0.5 "**Width W6 (metric)** 12.7 mm**Height H (Imperial)** 5.07 "**Height H (Metric)** 128.8 mm**Mounting Hole Centers (Imperial)** 4.0 "

### Logistics and Packaging

**Quantity Per** box**Package Quantity** 30.0 ft**Package Quantity (Metric)** 9.1 m**Carton Quantity** 120.0 ft

### Material and Specifications

**Material** Polyvinylchloride (PVC)

**Material Shortcut** PVC**Flammability** self-extinguishing**Operating Temperature** +122°F (+50°C)**ROHS Compliant** Yes**Certification/Specification** CSA

UL

**UL Listed (US and Canada)** No**UL Recognized (US)** Yes**UL Recognized (US and Canada)** No