

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)
[181-11004](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

HellermannTyton

181-11004

**Article Number: 181-11004****Solid Wall Wiring Duct, 1" X 1", Non-Adhesive, PVC, White, 30ft/Box**[Download drawing](#)[Download spec sheet](#)

Base Data

Local Order Number 181-11004**Type** SD1X1**Color** White (WH)**Features and Benefits**

- A temporary film is applied to the covers to protect against scratches and is writable for identification during installation.
- Cover is flush with the side of the duct for increased wire capacity and allows for tight, side by side duct placement.
- Covers are provided with a non-slip lining, which insures the covers remain in place during vibration, yet they easily snap on and off. (Covers to be purchased separately)

Product Description HellermannTyton's Pro-Duct, Solid Wall wiring duct efficiently routes and protects wire and cable. Solid Wall wiring duct is designed for straight wire runs where break outs are not required. Pro-Duct, Solid Wall wiring duct is manufactured from high impact, rigid PVC, comes in standard colors of white, gray and black, and is available in 6 foot lengths.**Short Description** Solid Wall Wiring Duct, 1" X 1", Non-Adhesive, PVC, White, 30ft/Box

Product Dimensions

Length L (Imperial) 6.0 ft**Length L (Metric)** 1.83 m**Width W (Imperial)** 1.0 "**Width W (Metric)** 25.4 mm**Width W2 (Imperial)** 1.0 "**Width W2 (Metric)** 25.4 mm**Height H (Imperial)** 1.06 "**Height H (Metric)** 26.9 mm**Mounting Hole Centers (Imperial)** 4.0 "

Logistics and Packaging

Quantity Per box**Package Quantity** 30.0 ft**Package Quantity (Metric)** 9.1 m**Carton Quantity** 120.0 ft

Material and Specifications

Material Polyvinylchloride (PVC)**Material Shortcut** PVC**Flammability** self-extinguishing

Operating Temperature +122°F (+50°C)

ROHS Compliant Yes

Certification/Specification UL
CSA

UL Listed (US and Canada) No

UL Recognized (US) Yes

UL Recognized (US and Canada) No