

## Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)  
[181-11501](#)

For any questions, you can email us directly:

[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)

# HellermannTyton

## 181-11501



**Article Number:** 181-11501

**Solid Wall Wiring Duct, 1" X 1.5", Non-Adhesive, PVC, Gray, 120ft/Carton**



Download drawing



Download spec sheet

### Base Data

**Local Order Number** 181-11501

**Type** SD1X1.5

**Color** Gray (GY)

**Features and Benefits**

- A temporary film is applied to the covers to protect against scratches and is writable for identification during installation.
- Cover is flush with the side of the duct for increased wire capacity and allows for tight, side by side duct placement.
- Covers are provided with a non-slip lining, which insures the covers remain in place during vibration, yet they easily snap on and off. (Covers to be purchased separately)

**Product Description** HellermannTyton's Pro-Duct, Solid Wall wiring duct efficiently routes and protects wire and cable. Solid Wall wiring duct it designed for straight wire runs where break outs are not required. Pro-Duct, Solid Wall wiring duct is manufactured from high impact, rigid PVC, comes in standard colors of white, gray and black, and is available in 6 foot lengths.

**Short Description** Solid Wall Wiring Duct, 1" X 1.5", Non-Adhesive, PVC, Gray, 120ft/Carton

### Product Dimensions

**Length L (Imperial)** 6.0 ft

**Length L (Metric)** 1.83 m

**Width W (Imperial)** 1.0 "

**Width W (Metric)** 25.4 mm

**Width W2 (Imperial)** 1.0 "

**Width W2 (Metric)** 25.4 mm

**Height H (Imperial)** 1.57 "

**Height H (Metric)** 39.9 mm

**Mounting Hole Centers (Imperial)** 4.0 "

### Logistics and Packaging

**Quantity Per** carton

**Package Quantity** 120.0 ft

**Package Quantity (Metric)** 36.6 m

**Carton Quantity** 120 ft

### Material and Specifications

**Material** Polyvinylchloride (PVC)

**Material Shortcut** PVC

**Flammability** self-extinguishing



**Operating Temperature** +122°F (+50°C)

**ROHS Compliant** Yes

**Certification/Specification** CSA  
UL

**UL Listed (US and Canada)** No

**UL Recognized (US)** Yes

**UL Recognized (US and Canada)** No