

## Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)  
[181-13007](#)

For any questions, you can email us directly:

[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)

# HellermannTyton

181-13007

Article Number: 181-13007

Slotted Wall Wiring Duct, 1" X 3", Non-Adhesive, PVC, White, 30ft/Box



Download drawing



Download spec sheet

## Base Data

Local Order Number 181-13007

Type SL1X3

Color White (WH)

**Features and Benefits**

- Strong fingers prevent unwanted breaking.
- Fingers are easily deflected outward, allowing ready positioning of the wires within the slotted wall duct.
- Restricted opening prevents unintended removal of wires and permits any individual wire to be traced without disconnection.

**Product Description** Pro-Duct slotted wall wiring duct features break-away fingers which provide additional access for wire leads. Each section of the duct is provided with two score lines. The upper score line is used to break away fingers when a wider opening is required. The lower score line allows the sidewall to be smoothly cut for joints and "Ts".

**Short Description** Slotted Wall Wiring Duct, 1" X 3", Non-Adhesive, PVC, White, 30ft/Box

## Product Dimensions

Length L (Imperial) 6.0 ft

Length L (Metric) 1.83 m

Width W (Imperial) 1.0 "

Width W (Metric) 25.4 mm

Width W2 (Imperial) 1.0 "

Width W2 (Metric) 25.4 mm

Width W3 (Imperial) 0.4 "

Width W3 (Metric) 10.2 mm

Width W4 (imperial) 1.0 "

Width W4 (metric) 25.4 mm

Width W5 (imperial) 2.6 "

Width W5 (metric) 66.0 mm

Height H (Imperial) 3.07 "

Height H (Metric) 77.9 mm

Mounting Hole Centers (Imperial) 4.0 "

## Logistics and Packaging

Quantity Per box

Package Quantity 30.0 ft

Package Quantity (Metric) 9.1 m

Carton Quantity 120.0 ft

## Material and Specifications

---

|                                      |                         |
|--------------------------------------|-------------------------|
| <b>Material</b>                      | Polyvinylchloride (PVC) |
| <b>Material Shortcut</b>             | PVC                     |
| <b>Flammability</b>                  | self-extinguishing      |
| <b>Operating Temperature</b>         | +122°F (+50°C)          |
| <b>ROHS Compliant</b>                | Yes                     |
| <b>Certification/Specification</b>   | CSA<br>UL               |
| <b>UL Listed (US and Canada)</b>     | No                      |
| <b>UL Recognized (US and Canada)</b> | No                      |
| <b>UL Recognized (US)</b>            | Yes                     |