

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

HellermannTyton 181-22017

For any questions, you can email us directly: <u>sales@integrated-circuit.com</u>



HellermannTyton

181-22017

 Article Number: 181-22017

 Solid Wall Wiring Duct, 2" X 2", Adhesive, PVC, White, 30ft/Box

 HellermannTyton

Download spec sheet

Base Data

Local Order Number	181-22017
Туре	SDA2X2
Color	White (WH)
Features and Benefits	 A temporary film is applied to the covers to protect against scratches and is writable for identification during installation. Cover is flush with the side of the duct for increased wire capacity and allows for tight, side by side duct placement. Covers are provided with a non-slip lining, which insures the covers remain in place during vibration, yet they easily snap on and off. (Covers to be purchased separately)
Product Description	HellermannTyton's Pro-Duct, Solid Wall wiring duct efficiently routes and protects wire and cable. Solid Wall wiring duct it designed for straight wire runs where break outs are not required. Pro-Duct, Solid Wall wiring duct is manufactured from high impact, rigid PVC, comes in standard colors of white, gray and black, and is available in 6 foot lengths.
Short Description	Solid Wall Wiring Duct, 2" X2", Adhesive, PVC, White, 30ft/Box

Product Dimensions

Length L (Imperial)	6.0 ft
Length L (Metric)	1.83 m
Width W (Imperial)	2.0 "
Width W (Metric)	50.8 mm
Width W2 (Imperial)	2.0 "
Width W2 (Metric)	50.8 mm
Width W6 (imperial)	0.5 "
Width W6 (metric)	12.7 mm
Height H (Imperial)	2.07 "
Height H (Metric)	52.6 mm
Mounting Hole Centers (Imperial)	4.0 "

Logistics and Packaging

Quantity Per	box
Package Quantity	30.0 ft
Package Quantity (Metric)	9.1 m
Carton Quantity	120.0 ft

Material and Specifications

Matorial	Polyvinylchloride (PVC)	



Material Shortcut	PVC
Flammability	self-extinguishing
Operating Temperature	+122°F (+50°C)
ROHS Compliant	Yes
Certification/Specification	UL CSA
UL Listed (US and Canada)	No
UL Recognized (US)	Yes
UL Recognized (US and Canada)	No

© HellermannTyton 2015