

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)

[181-44009](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

HellermannTyton

181-44009

**Article Number: 181-44009****Solid Wall Wiring Duct, 4" X 4", Non-Adhesive, PVC, Gray, 120ft /Carton**

Download drawing

Download spec sheet

Base Data

Local Order Number 181-44009**Type** SD4X4**Color** Gray (GY)**Features and Benefits**

- A temporary film is applied to the covers to protect against scratches and is writable for identification during installation.
- Cover is flush with the side of the duct for increased wire capacity and allows for tight, side by side duct placement.
- Covers are provided with a non-slip lining, which insures the covers remain in place during vibration, yet they easily snap on and off. (Covers to be purchased separately)

Product Description HellermannTyton's Pro-Duct, Solid Wall wiring duct efficiently routes and protects wire and cable. Solid Wall wiring duct is designed for straight wire runs where break outs are not required. Pro-Duct, Solid Wall wiring duct is manufactured from high impact, rigid PVC, comes in standard colors of white, gray and black, and is available in 6 foot lengths.**Short Description** Solid Wall Wiring Duct, 4" X4", Non-Adhesive, PVC, Gray, 120ft /Carton

Product Dimensions

Length L (Imperial) 6.0 ft**Length L (Metric)** 1.83 m**Width W (Imperial)** 4.0 "**Width W (Metric)** 101.6 mm**Width W2 (Imperial)** 4.0 "**Width W2 (Metric)** 101.6 mm**Width W6 (imperial)** 1.5 "**Width W6 (metric)** 38.1 mm**Height H (Imperial)** 4.07 "**Height H (Metric)** 103.4 mm**Mounting Hole Centers (Imperial)** 4.0 "

Logistics and Packaging

Quantity Per carton**Package Quantity** 120.0 ft**Package Quantity (Metric)** 36.6 m**Carton Quantity** 120.0 ft

Material and Specifications

Material Polyvinylchloride (PVC)

Material Shortcut PVC

Flammability self-extinguishing

Operating Temperature +122°F (+50°C)

ROHS Compliant Yes

Certification/Specification CSA

UL

UL Listed (US and Canada) No

UL Recognized (US and Canada) No

UL Recognized (US) Yes