

## **Excellent Integrated System Limited**

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

HellermannTyton 181-45001

For any questions, you can email us directly: <u>sales@integrated-circuit.com</u>



## HellermannTyton

### 181-45001

Art	icle Number: 181-45001
So	lid Wall Wiring Duct, 4" X 5", Non-Adhesive, PVC, White, 60ft/Carton
	RoHS
Download drawing	spec sheet
Base Data	
Local Order Number	181-45001
Туре	SD4X5
Color	White (WH)
Features and Benefits	<ul> <li>A temporary film is applied to the covers to protect against scratches and is writable for identification during installation.</li> <li>Cover is flush with the side of the duct for increased wire capacity and allows for tight, side by side duct placement.</li> <li>Covers are provided with a non-slip lining, which insures the covers remain in place during vibration, yet they easily snap on and off. (Covers to be purchased separately)</li> </ul>
Product Description	HellermannTyton's Pro-Duct, Solid Wall wiring duct efficiently routes and protects wire and cable. Solid Wall wiring duct it designed for straight wire runs where break outs are not required. Pro-Duct, Solid Wall wiring duct is manufactured from high impact, rigid PVC, comes in standard colors of white, gray and black, and is available in 6 foot lengths.
Short Description	Solid Wall Wiring Duct, 4" X 5", Non-Adhesive, PVC, White, 60ft/Carton
Product Dimensions	
Length L (Imperial)	6.0 ft
Length L (Metric)	1.83 m
Width W (Imperial)	4.0 "
Width W (Metric)	101.6 mm
Width W2 (Imperial)	4.0 "
Width W2 (Metric)	101.6 mm
Width W6 (imperial)	1.5 "
Width W6 (metric)	38.1 mm
Height H (Imperial)	5.07 "
Height H (Metric)	128.8 mm
Mounting Hole Centers (Imperial)	4.0 "
Logistics and Packaging	

# Quantity Per carton Package Quantity 60.0 ft Package Quantity (Metric) 18.3 m Carton Quantity 60.0 ft

#### **Material and Specifications**

Material	Polyvinylchloride	(PVC)



Material Shortcut	PVC
Flammability	self-extinguishing
Operating Temperature	+122°F (+50°C)
<b>ROHS</b> Compliant	Yes
Certification/Specification	UL CSA
UL Listed (US and Canada)	No
UL Recognized (US)	Yes
UL Recognized (US and Canada)	No

© HellermannTyton 2015