

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)
[1FRP9C](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

HellermannTyton

1FRP9C



Article Number: 161-05001

Spiralwrap, 1/8" Diameter, PE-FR, Natural, 100ft/RL



Download spec sheet

Base Data

Local Order Number 1FRP9C

Type 1FRP

Color Natural (NA)

- Features and Benefits**
- Sheathing allows flexible routing and lead-out of cables
 - The inner edges are beveled preventing damage to cables
 - Sheathing is reusable and resistant to most chemicals
 - Spiralwrap is U.L. Recognized

Product Description HellermannTyton's Spiralwrap protective sheathing provides cable protection and flexible routing. Spiralwrap is wrapped around a group of cables to shield and organize.

Short Description Spiralwrap, 1/8" Diameter, PE-FR, Natural, 100ft/RL

Product Dimensions

Length L (Imperial) 100.0 ft

Length L (Metric) 30.48 m

Reel Length (imperial) 100.0 ft

Variant Spiral Binding

Bundle Diameter Min. (Imperial) 0.06 "

Bundle Diameter Min. (Metric) 1.6 mm

Bundle Diameter Max. (Imperial) 0.5 "

Bundle Diameter Max. (Metric) 12.7 mm

Diameter D (imperial) 0.125 "

Diameter D (metric) 3.18 mm

Nominal Diameter (Imperial) 1/8 "

Nominal Diameter (Metric) 3.18 mm

Wall Thickness WT (Imperial) 0.032 "

Wall Thickness WT (Metric) 0.81 mm

Pitch (imperial) 0.187 "

Pitch (metric) 4.75 mm

Logistics and Packaging

Quantity Per reel

Package Quantity 100.0 ft

Package Quantity (Metric) 30.48 m



Material and Specifications

Material	Polyethylene, flame retardant (PE-FR)
Material Shortcut	PE-FR
Flammability	UL94 V0
Operating Temperature	-4°F to +176°F (-20°C to +80°C)
ROHS Compliant	Yes
UL Recognized (US)	Yes