



**Distributor of HellermannTyton: Excellent Integrated System Limited**

Datasheet of 211-60002 - PCLAMP .3937" MAXBUNDIA .255"

Contact us: [sales@integrated-circuit.com](mailto:sales@integrated-circuit.com) Website: [www.integrated-circuit.com](http://www.integrated-circuit.com)

---

## **Excellent Integrated System Limited**

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)  
[211-60002](#)

For any questions, you can email us directly:

[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)

# HellermannTyton

## 211-60002



**Article Number: 211-60002**

**P Clamp, .39" Width, .26" Max Bundle Dia, .17" Mounting Hole Dia, PA66HS, Black, 100/pkg**



Download drawing



Download spec sheet

### Base Data

**Local Order Number** 211-60002

**Type** H3P

**Color** Black (BK)

**Features and Benefits**

- P-Clamps easily guide and locate wire and cables up to 1" in diameter.
- Designed with a radiused edge to prevent chaffing and cutting into insulation.

**Product Description** HellermannTyton P Clamps easily guide and locate wires and cables. The clamps are designed with a radiused edge to prevent chaffing and cutting into insulation. Available sizes up to 1" bundle diameters.

**Short Description** P Clamp, .39" Width, .26" Max Bundle Dia, .17" Mounting Hole Dia, PA66HS, Black, 100/pkg

### Product Dimensions

**Fixation Method** screw-hole

**Variant** Closed

**Width W (Imperial)** 0.39 "

**Width W (Metric)** 10.0 mm

**Bundle Diameter Max. (Imperial)** 0.26 "

**Bundle Diameter Max. (Metric)** 6.5 mm

**Mounting Hole Diameter D (Imperial)** 0.17 "

**Mounting Hole Diameter D (Metric)** 4.2 mm

**Nominal Diameter (Imperial)** 1/4 "

**Nominal Diameter (Metric)** 6.5 mm

**Wall Thickness WT (Imperial)** .03937 "

**Wall Thickness WT (Metric)** 1.0 mm

**Mounting Hole Centers (Imperial)** 0.39 "

**Mounting Hole Diameter D Max.** 4.2 mm

**(Metric) Mounting Hole Diameter D Min. (Metric)** 4.2 mm

### Logistics and Packaging

**Quantity Per** bag

**Package Quantity (Metric)** 100 Pieces

**Carton Quantity** 5000 Pieces

**Weight (Metric)** 0.4 kg

### Material and Specifications



**Material** Polyamide 6.6 heat stabilized (PA66HS)

**Material Shortcut** PA66HS

**Flammability** UL94 V2

**Operating Temperature** -40°F to +221°F (-40°C to +105°C)

**ROHS Compliant** Yes