



Distributor of HellermannTyton: Excellent Integrated System Limited

Datasheet of 211-60160 - PCLAMP .4724" MAXBUNDIA 1.003"

Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)

[211-60160](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

HellermannTyton

211-60160



Article Number: 211-60160

P Clamp, .47" Width, 1" Max Bundle Dia, .2" Mounting Hole Dia, PA66HS, Black, 1000/pkg



Download drawing



Download spec sheet

Base Data

Local Order Number 211-60160

Type H15P

Color Black (BK)

Features and Benefits

- P-Clamps easily guide and locate wire and cables up to 1" in diameter.
- Designed with a radiused edge to prevent chaffing and cutting into insulation.

Product Description HellermannTyton P Clamps easily guide and locate wires and cables. The clamps are designed with a radiused edge to prevent chaffing and cutting into insulation. Available sizes up to 1" bundle diameters.

Short Description P Clamp, .47" Width, 1" Max Bundle Dia, .2" Mounting Hole Dia, PA66HS, Black, 1000/pkg

Product Dimensions

Fixation Method screw-hole

Variant Closed

Width W (Imperial) 0.47 "

Width W (Metric) 12.0 mm

Bundle Diameter Max. (Imperial) 1.0 "

Bundle Diameter Max. (Metric) 25.5 mm

Mounting Hole Diameter D (Imperial) 0.2 "

Mounting Hole Diameter D (Metric) 5.2 mm

Nominal Diameter (Imperial) 1 "

Nominal Diameter (Metric) 25.5 mm

Wall Thickness WT (Imperial) .05906 "

Wall Thickness WT (Metric) 1.5 mm

Mounting Hole Centers (Imperial) 0.91 "

Mounting Hole Diameter D Max. 5.2 mm

(Metric) Mounting Hole Diameter D Min. (Metric) 5.2 mm

Logistics and Packaging

Quantity Per bag

Package Quantity (Metric) 1000 Pieces

Carton Quantity 5000 Pieces

Weight (Metric) 2 kg

Material and Specifications



Distributor of HellermannTyton: Excellent Integrated System Limited

Datasheet of 211-60160 - PCLAMP .4724" MAXBUNDIA 1.003"

Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

Material Polyamide 6.6 heat stabilized (PA66HS)

Material Shortcut PA66HS

Flammability UL94 V2

Operating Temperature -40°F to +221°F (-40°C to +105°C)

ROHS Compliant Yes