



## **Excellent Integrated System Limited**

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)  
[553-50192](#)

For any questions, you can email us directly:  
[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)

# HellermannTyton

553-50192

**Article Number: 553-50192**

**Heat Shrink Label, .5" Unslit, Single Sided, Polyolefin, White, 1000/BX**



Download spec sheet

## Base Data

**Local Order Number** 553-50192

**Type** HST9-3WH

**Color** White (WH)

- Features and Benefits**
- Slide Slit and optional center slits for easy wire insertion.
  - Smooth surface for clean and legible printing.
  - Supplied on a ladder style carrier so that markers can be kitted after printing.
  - A 3:1 shrink ratio means fewer skews as each marker covers a wider range of wire diameters.

**Product Description** HellermannTyton's ShrinkTrak heat shrinkable markers make it easy to mark wire, cable and other components. The military approved heat shrink tubing is flattened and assembled in a ladder style carrier system for easy printing using a thermal transfer printer. The ladder system creates a kit of markers that can be sorted, removed and applied in any order thus saving time, labor and speeding production.

**Short Description** Heat Shrink Label, .5" Unslit, Single Sided, Polyolefin, White, 1000/BX

## Product Dimensions

**Length L (Imperial)** 0.597 "

**Length L (Metric)** 15.16 mm

**Printable (Yes/No)** Yes

**Variant** Thin-Wall

**Width W (Imperial)** 1.90 "

**Width W (Metric)** 48 mm

**Height H (Imperial)** 0.597 "

**Height H (Metric)** 15.16 mm

**Diameter Max. (Imperial)** 0.375 "

**Outside Diameter Max. (Imperial)** 0.375 "

**Outside Diameter Max. (Metric)** 9.52 mm

**Wall Thickness WT (Imperial)** 0.033 "

**Wall Thickness WT (Metric)** 0.80 mm

**Print Method** Thermal Transfer

**Recovered Diameter d (metric)** 3.0 mm

**Recovered Diameter d (imperial)** 0.122 "

**Supplied Diameter D (metric)** 9.0 mm

**Supplied Diameter D (imperial)** 0.354 "

**Thickness T (Metric)** 3.0 µm

**Width of Liner WL (imperial)** 3.0 "

**Width of Liner WL (metric)** 76.2 mm

**Width of Printable Area (imperial)** 1.9 "

**Width of printable area (metric)** 48.26 mm

## Logistics and Packaging

---

**Quantity Per** box

**Package Quantity** 1000

**Package Quantity (Metric)** 1000

**Carton Quantity** 1 Pack

**Markers per row** 1

**Weight (imperial)** 3.72

**Weight (Metric)** 1.72 kg

## Material and Specifications

---

**Material** Polyolefin, cross-linked (PO-X)

**Material Shortcut** PO-X

**Dielectric Strength (Metric)** 19.7 kV min.

**Flammability** UL224 VW-1

**Shrink Temperature** +194 °F (+90 °C)

**Operating Temperature** -67°F to +275°F (-55°C to +135°C)

**ROHS Compliant** Yes

**Certification/Specification** UL224 125 °C 600V VW-1  
SAE - AMS - DTL-23053/5 Class 1 and 3  
SAE-AS81531  
MIL-STD-202G Method 215K