

## **Excellent Integrated System Limited**

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)  
[556-26008](#)

For any questions, you can email us directly:  
[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)

# HellermannTyton

556-26008

Article Number: 556-26008

TipTag, 2.59" X .68", Polyolefin/Polyester, White/Yellow, 500/RL



Download drawing



Download spec sheet

## Base Data

Local Order Number 556-26008

Type TIPTAGVA15X65YEWH

Color White (WH)  
Yellow (YE)

**Features and Benefits**

- Halogen Free for low smoke and low fire hazard applications.
- White front and yellow back for versatility.
- Superior strength and tear resistance for long lasting identification.
- Pre-cut slots to secure the TipTags using HellermannTyton cable ties.

**Product Description** TIPTAGs are halogen free, tear resistant, and lightweight cross laminated polyolefin tags ideal for use where weight is a critical factor. Each side is a different color. One side is yellow and the other side is White so that a high contrast black on yellow or black on white mark can be printed.

Mounting method Identification ETIM Others

Short Description TipTag, 2.59" X .68", Polyolefin/Polyester, White/Yellow, 500/RL

## Product Dimensions

Length L (Imperial) 0.6875 "

Length L (Metric) 17.4 mm

Self adhesive (Yes/No) No

Variant Other

Width W (Imperial) 2.59 "

Width W (Metric) 65.0 mm

Height of printable area (imperial) .59 "

Height of printable area (metric) 15 mm

Print Method Thermal Transfer

Width of Printable Area (imperial) 2.58 "

Width of printable area (metric) 65.00 mm

## Logistics and Packaging

Quantity Per reel

Package Quantity 500

Package Quantity (Metric) 500 Pieces

Weight (Metric) 0.25 kg

## Material and Specifications



**Material Shortcut** PO

**Halogenfree** Yes

**Operating Temperature** -58°F to +221°F (-50°C to +105°C)

**ROHS Compliant** Yes

**Certification/Specification** SAE-AS81531  
BS-4G-198-3, Type 11a  
MIL-STD-202G Method 215K