

## **Excellent Integrated System Limited**

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)

[558-00374](#)

For any questions, you can email us directly:

[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)

# HellermannTyton

558-00374

Article Number: 558-00374

Solid Colored Continuous Roll, 3.0" X 250', Vinyl, Black, 250ft/RL



Download drawing



Download spec sheet

## Base Data

Local Order Number 558-00374

Type HT3BK250

Color Black (BK)

- Features and Benefits**
- Continuous Vinyl Labels are made with UV stable materials for long outdoor life.
  - Labels are extruded in the actual color and not colored using surface inks for long term fade resistance.
  - Continuous Vinyl is provided in continuous rolls so that the markers can be printed and cut to any length using HellermannTyton thermal transfer printing systems.

**Product Description** HellermannTyton continuous vinyl labels come in a variety of colors and printing widths. The vinyl is UV stable and has been tested to 20 years outdoor durability in Xenon Arc testing. The labels can be printed and cut to any length to create a wide variety custom label designs, on demand and using standard thermal transfer printing equipment. Each roll contains 250 feet (76M) of high performance vinyl.

**Short Description** Solid Colored Continuous Roll, 3.0" X 250', Vinyl, Black, 250ft/RL

## Product Dimensions

Length L (Imperial) 250.0 ft

Length L (Metric) 76.2 m

Width W (Imperial) 3.0 "

Width W (Metric) 76.2 mm

Height H (Imperial) 3.0 "

Height H (Metric) 76.2 mm

Print Method Thermal Transfer

Vertical Repeat VR (imperial) 3.0 "

Vertical Repeat VR (metric) 76.2 mm

Width of Liner WL (metric) 76.2 mm

Width of Liner WL (imperial) 3.0 "

## Logistics and Packaging

Quantity Per reel

Package Quantity 250

Package Quantity (Metric) 250 ft

Labels per Column 1

Labels per Row 1

## Material and Specifications



**Material Shortcut** VL

**Adhesive** Acrylic

**Adhesive Shortcut** Acrylic

**Adhesive Operating Temperature** -40°F to +180°F (-40°C to +82°C)

**Operating Temperature** -40°F to +180°F (-40°C to +82°C)

**ROHS Compliant** Yes