

## Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)

[596-00241](#)

For any questions, you can email us directly:


[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)

# HellermannTyton

596-00241

Article Number: 596-00241

Printable Solar Label, DC RATING LABEL, 3.75" X 2.0", Polyester, Red, 50/RL



Download spec sheet

## Base Data

Local Order Number 596-00241

Type DCRATING

Color Red (RD)

- Features and Benefits**
- Made with UV stable inks and materials for durability and weather resistance.
  - The labels are supplied with aggressive adhesive to ensure long life.
  - Solar Installation labels meet NEC & IFC standards for printed text, character height, color and outdoor UV stability to pass inspections.

**Product Description** HellermannTyton pre-printed Solar Installation labels are designed to meet the requirements of the 2014 National Electrical Code (NEC 2014) and the 2012 International Fire Code (IFC 2012) as well as being acceptable to the Authority Having Jurisdiction (AHJ). Labels are made with durable UV stable materials and adhesives that are designed to stick to both baked enamel and powder coat surfaces. Where applicable, labels are made using reflective materials for first responder safety. Some pre-printed labels are printable using a thermal transfer printer when variable voltage or series data must be printed and displayed.

**Technical Description** 3.75" X2" White text on red background that reads as: "PV SYSTEM DC DISCONNECT; OPERATING CURRENT; OPERATING VOLTAGE; MAXIMUM SYSTEM VOLTAGE; SHORT CIRCUIT CURRENT." 50 per roll. Label is also printable using a thermal transfer printer to add the variable voltage information on demand.

Local Order Number 2 Spanish Version: 596-00815

Short Description Printable Solar Label, DC RATING LABEL, 3.75" X 2.0", Polyester, Red, 50/RL

## Product Dimensions

Length L (Imperial) 3.75 "

Length L (Metric) 92.25 mm

Width W (Imperial) 3.75 "

Width W (Metric) 92.25 mm

Height H (Imperial) 2.0 "

Height H (Metric) 50.8 mm

## Logistics and Packaging

Quantity Per roll

Package Quantity 50

Package Quantity (Metric) 50

Labels per Column 1

Labels per Row 1

## Material and Specifications

Material Type 840/926 Polyester (PET) white (WH) UV stable w/ clear Polyester laminate



**Material Shortcut** 840/926

**Adhesive Shortcut** Acrylic

**Adhesive** Acrylic

**Adhesive Operating Temperature** -40°F to +180°F (-40°C to +82°C)

**Halogenfree** Yes

**Operating Temperature** -40°F to +302°F (-40°C to +150°C)

**ROHS Compliant** Yes

**Certification/Specification** UL969

**UL Recognized (US)** Yes