

## Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)

[596-00245](#)

For any questions, you can email us directly:

[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)

# HellermannTyton

596-00245

Article Number: 596-00245

Pre-Printed Reflective Solar Label, 6.5" X 1", CAUTION: SOLAR ELECTRIC SYSTEM...,Red, 50/pkg



Download drawing



Download spec sheet

## Base Data

Local Order Number 596-00245

Type CSESC

Color Red (RD)

**Features and Benefits**

- Made with UV stable inks and materials for durability and weather resistance.
- The labels are supplied with aggressive adhesive to ensure long life.
- Solar Installation labels meet NEC & IFC standards for printed text, character height, color and outdoor UV stability to pass inspections.

**Product Description** HellermannTyton pre-printed Solar Installation labels are designed to meet the requirements of the 2014 National Electrical Code (NEC 2014) and the 2012 International Fire Code (IFC 2012) as well as being acceptable to the Authority Having Jurisdiction (AHJ). Labels are made with durable UV stable materials and adhesives that are designed to stick to both baked enamel and powder coat surfaces. Where applicable, labels are made using reflective materials for first responder safety. Some pre-printed labels are printable using a thermal transfer printer when variable voltage or series data must be printed and displayed.

**Technical Description** 6.5" X 1" White text on a red background that reads as: "CAUTION - SOLAR ELECTRIC SYSTEM CONNECTED" in 3/8" tall characters using reflective inks. 50 per pkg.

**Short Description** Pre-Printed Reflective Solar Label, 6.5" X 1", CAUTION: SOLAR ELECTRIC SYSTEM...,Red, 50/pkg

## Product Dimensions

Width W (Imperial) 6.5 "

Width W (Metric) 165.1 mm

Height H (Imperial) 1.0 "

Height H (Metric) 25.4 mm

## Logistics and Packaging

Quantity Per reel

Package Quantity 50

Package Quantity (Metric) 50

## Material and Specifications

Material Vinyl

Material Shortcut VL

Adhesive Shortcut Acrylic

Adhesive Acrylic

Adhesive Operating Temperature -40°F to +302°F (-40°C to +150°C)

Halogenfree Yes



**Distributor of HellermannTyton: Excellent Integrated System Limited**

Datasheet of 596-00245 - CAUTION LABEL 50/PK

Contact us: [sales@integrated-circuit.com](mailto:sales@integrated-circuit.com) Website: [www.integrated-circuit.com](http://www.integrated-circuit.com)

---

**ROHS Compliant** Yes

**UL Recognized (US)** Yes