

## Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)  
[FA1SMSTST](#)

For any questions, you can email us directly:

[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)

# HellermannTyton

## FA1SMSTST



**Article Number: 855-34210**

**ST - ST Simplex Single mode Fiber Assembly, 1M, Yellow, 1/pkg**



Download spec sheet

### Base Data

**Local Order Number** FA1SMSTST

**Type** FASMSTST

**Color** Yellow (YE)

- Features and Benefits**
- Pre-radiused zirconia ceramic ferrules for precision alignment.
  - Industry standard ST, SC, MTRJ or LC connectors to suit specific applications.
  - Available in 1-5 meter lengths for a variety of applications.
  - Color coded for easy identification.
  - Individually quality tested for insertion and return loss.
  - Meet ANSI/TIA/EIA 568-B standards.
  - Meet ANSI/TIA/EIA 604 (FOCIS) connector interface requirements.

**Product Description** For fiber patching requirements, HellermannTyton offers fiber optic jumpers in various lengths with a wide variety of connector configurations. HellermannTyton offers fiber jumpers in two types – standard and high performance. Our standard jumpers combine quality with value. They meet all ANSI/TIA/EIA fiber optic cable requirements while allowing installers to maximize project budgets. In addition to meeting industry standards, HellermannTyton high performance jumpers have additional features designed for high performance applications . Our high performance jumpers meet Trade Agreement Act (TAA) requirements, making them suitable for use in General Services Administration (GSA) government contract projects.

**Short Description** ST - ST Simplex Single mode Fiber Assembly, 1M, Yellow, 1/pkg

### Product Dimensions

**Length L (Imperial)** 3.3 ft

**Length L (Metric)** 1.0 m

**Length L2 (Imperial)** 39.4 "

### Logistics and Packaging

**Quantity Per** bag

**Package Quantity** 1

**Package Quantity (Metric)** 1

### Material and Specifications

**Optical Performance** Singlemode