

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)
[IT50R0C2](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

HellermannTyton

IT50R0C2



Article Number: 111-85011

Identification Tie, 8" Long, 50lb Tensile Strength, PA66, Black, 100/pkg



Download spec sheet

Base Data

Local Order Number IT50R0C2

Type IT50R

Color Black (BK)

Features and Benefits

- Identification plate feature allows bundles to be easily marked and identified.
- Wire and cable harnesses can be secured and identified using just one product, which saves time.
- Plates can be marked manually with a permanent marker or with a pre-printed adhesive label.

Product Description HellermannTyton Identification cable ties feature an identification plate allowing wire and cable bundles to be easily marked and identified. These ties enable wire and cables to be secured and identified using just one product, saving installation time. The plates can be marked using a permanent marker or with a HellermannTyton adhesive label.

Mounting method Identification ETIM Others

Short Description Identification Tie, 8" Long, 50lb Tensile Strength, PA66, Black, 100/pkg

Product Dimensions

Minimum Tensile Strength (Imperial) 50.0 lbs

Minimum Tensile Strength (Metric) 225.0 N

Length L (Imperial) 8.0 "

Length L (Metric) 203.0 mm

Fixation Method None

Identification Plate Position attached to bundle

Tie Closure plastic pawl

Variant Inside Serrated

Width W (Imperial) 1.1 "

Width W (Metric) 28.0 mm

Width W2 (Imperial) 0.18 "

Width W2 (Metric) 4.6 mm

Height H (Imperial) 0.51 "

Height H (Metric) 12.9 mm

Bundle Diameter Min. (Imperial) 0.37 "

Bundle Diameter Min. (Metric) 9.5 mm

Bundle Diameter Max. (Imperial) 1.8 "

Bundle Diameter Max. (Metric) 44.5 mm

Outside Diameter Min. (Imperial) 0.37 "

Outside Diameter Min. (Metric) 9.50 mm



Outside Diameter Max. (Metric) 44.50 mm

Logistics and Packaging

Quantity Per bag
Package Quantity (Metric) 100
Carton Quantity 5000

Material and Specifications

Material Polyamide 6.6 (PA66)
Material Shortcut PA66
Flammability UL94 V2
Halogenfree Yes
Operating Temperature -40°F to +185°F (-40°C to +85°C)
ROHS Compliant Yes
Certification/Specification UL
UL Listed (US and Canada) No
UL Recognized (US and Canada) Yes