Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

HellermannTyton
LTM2500C2

For any questions, you can email us directly:
sales@integrated-circuit.com

HellermannTyton

LTM2500C2

Article Number: 151-00358

Lashing Tie Mount, 0.73" x 1.5", 0.25" Screw, PA66HS, Black, 100/pkg

RoHS

Download drawing Download spec sheet

Base Data

Local Order Number	LTM2500C2
Type	LTM250
Color	Black (BK)
Features and Benefits	• The strap is parallel to the mount when inserted into the head, providing a mounting point for where the cable ties.
Product Description	The Lashing Tie Mount is designed to snap into the T250 lashing tie. The tie head is assembled perpendicular to the mount. The lashing tie mount is recommended for indoor or outdoor wall mount cable applications.
Short Description	Lashing Tie Mount, 0.73" x 1.5", 0.25" Screw, PA66HS, Black, 100/pkg

Product Dimensions

Length L (Imperial)	1.5 "
Length L (Metric)	37.1 mm
Fixation Method	Screw Mounting and Rivet
Width W (Imperial)	0.73 "
Width W (Metric)	18.5 mm
Cable Tie Width Max. (Imperial)	0.49 "
Cable Tie Width Max. (Metric)	12.5 mm
Height H (Imperial)	0.38 "
Height H (Metric)	9.6 mm
Mounting Hole Diameter D (Imperial)	0.26 "
Mounting Hole Diameter D (Metric)	6.6 mm
Mounting Hole Diameter D Max. (Metric)	6.6 mm
Mounting Hole Diameter D Min. (Metric)	6.6 mm

Logistics and Packaging

Quantity Per	bag
Package Quantity (Metric)	100
Carton Quantity	3000

Material and Specifications

Material	Polyamide 6.6 heat stabilized (PA66HS)
Material Shortcut	PA66HS
Flammability	UL94 V2
Operating Temperature	-40°F to +221°F (-40°C to +105°C)

ROHS Compliant	Yes

© HellermannTyton 2015