

## Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)  
[MB2.5A0M4](#)

For any questions, you can email us directly:

[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)

# HellermannTyton

## MB2.5A0M4



Article Number: 151-29001

Adhesive Bases, .1" Max tie width, .625" Length/Width, .11" Hole Dia., PA66, Black, 1000/pkg



Download drawing



Download spec sheet

### Base Data

Local Order Number MB2.5A0M4

Type MB2.5A

Color Black (BK)

- Features and Benefits**
- For use with 18 pound cable ties to provide stability when securing bundles.
  - Secures with rubber based adhesive backing and/or two or four screws.
  - 4 way opening allows cable ties to be installed parallel or perpendicular to wire bundles.

**Product Description** HellermannTyton adhesive fastened mounting bases are used with 18 through 150 pound cable ties to provide stability when securing bundles. The mounts are installed using the adhesive backing and/or by securing two or four screws. The 4 way opening allows the cable ties to be inserted parallel or perpendicular to the wire bundles.

**Short Description** Adhesive Bases, .1" Max tie width, .625" Length/Width, .11" Hole Dia., PA66, Black, 1000/pkg

### Product Dimensions

Length L (Imperial) 0.625 "

Length L (Metric) 15.9 mm

Fixation Method Screw Mounting and Adhesive

Width W (Imperial) 0.625 "

Width W (Metric) 15.9 mm

Cable Tie Width Max. (Imperial) 0.1 "

Cable Tie Width Max. (Metric) 2.54 mm

Height H (Imperial) 0.16 "

Height H (Metric) 4.1 mm

Mounting Hole Diameter D (Imperial) 0.11 "

Mounting Hole Diameter D (Metric) 2.8 mm

Thickness of Adhesive TA (Imperial) 0.031 "

Mounting Hole Diameter D Max. 2.8 mm

(Metric) Mounting Hole Diameter D Min. (Metric) 2.8 mm

Thickness of Adhesive TA (Metric) 0.8 mm

### Logistics and Packaging

Quantity Per bag

Package Quantity (Metric) 1000

Carton Quantity 10000

### Material and Specifications

**Material** Polyamide 6.6 (PA66)

**Material Shortcut** PA66

**Adhesive Shortcut** Synthetic rubber T50

**Adhesive** Synthetic rubber with base of polyethylene foam

**Adhesive Operating Temperature** -4°F to +122°F (-20°C to +50°C)

**Flammability** UL94 V2 (excluding adhesive)

**Operating Temperature** -40°F to +185°F (-40°C to +85°C)

**ROHS Compliant** Yes

**UL Listed (US and Canada)** No

**UL Recognized (US and Canada)** Yes