Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

HellermannTyton
PP24SMOD6ASRS

For any questions, you can email us directly:
sales@integrated-circuit.com

HellermannTyton

PP24SMOD6ASRS

Article Number: 853-55001

Category 6A 24 Port Sliding Shielded Patch Panel With Rack-Snaps, 1U, 1/box

Download spec sheet

Base Data

Local Order Number	PP24SMOD6ASRS
Type	PP24G6A-PA1URS-SL.XX
Color	Black (BK)
Features and Benefits	• Integral earthing plate grounds each keystone jack helping to guarantee 10G performance by giving continuity of the 360° shielding.
	• To ease installation, panels are offered with Rack-Snap inserts which dramatically reduce installation time as they eliminate the need for tools and cage nuts in standard EIA-310-D standard racks or cabinets with square holes.
	• Sliding feature allows better access to insert the jack providing easier installation.
Product Description	HellermannTyton's Category 6A shielded patch panels accept HellermannTyton Shielded Category 6A jacks (RJ45FC6AS) to complete a shielded system solution. The panel provides a choice of ground stud positions on the integral grounding bar and includes rear cable management. Panels are offered in two styles, a fixed version or a sliding version to ease installation.
Technical Description	The Deca¹⁰ copper solution is designed using S-FTP Category 6A cable which provides 360° shielding and eliminates alien crosstalk.
	The Deca¹⁰ Category 6A panel accommodates 24 Category 6A Keystone Jacks 1U.
	The integral earthing plate grounds each Keystone Jack helping to guarantee 10G performance by giving continuity of the 360° shielding.
	Tested to exceed ISO/EIA 11801:2002 amendment 1.1 and ANSI/TIA/EIA 568 - C.2 standards, the Deca¹⁰ Category 6A panel offers backward compatibility with Category 6, Category 5e, Category 5 and voice products.
Short Description	Category 6A 24 Port Sliding Shielded Patch Panel With Rack-Snaps, 1U, 1/box

Product Dimensions

Height in Units	1U
Performance Category	Category 6A (Class EA)
Port count	24
Width W (Imperial)	19.0 "
Width W (Metric)	483.0 mm
Height H (Imperial)	1.7 "
Height H (Metric)	44.0 mm
Depth D (metric)	192.0 mm
Depth D (imperial)	7.56 "

Logistics and Packaging

Package Quantity	1
Package Quantity (Metric)	1
Carton Quantity	1

Material and Specifications