

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)
[RT250I9X2](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

HellermannTyton

RT250I9X2



Article Number: 131-75219

Releasable Cable Tie, 28.7" Long, 250 lb Tensile Strength, PA66, Natural, 25/pkg



Download drawing



Download spec sheet

Base Data

Local Order Number RT250I9X2

Type RT250I

Color Natural (NA)

- Features and Benefits**
- Special design offers a release feature for quick and easy access to wire bundles.
 - Head design provides high tensile strength with very low insertion force even after repeated use.
 - Buckle feature on head allows excess strap to be tucked away after installation.

Product Description HellermannTyton releasable cable ties offer a release feature in the head allowing for easy access to wire bundles when changes are necessary. The head design guarantees high tensile strength even after repeated use, as well as a low insertion force. For high volume applications, tensioning tools are available to ensure consistent and safe installation.

Short Description Releasable Cable Tie, 28.7" Long, 250 lb Tensile Strength, PA66, Natural, 25/pkg

Product Dimensions

Minimum Tensile Strength (Imperial) 250.0 lbs

Minimum Tensile Strength (Metric) 1115.0 N

Length L (Imperial) 28.7 "

Length L (Metric) 730.0 mm

Fixation Method None

Identification Plate Position none

Releasable Closure Yes

Tie Closure plastic pawl

Variant Inside Serrated

Width W (Imperial) 0.49 "

Width W (Metric) 12.5 mm

Cable Tie Width Max. (Imperial) 0.49 "

Cable Tie Width Max. (Metric) 12.5 mm

Bundle Diameter Min. (Imperial) 0.47 "

Bundle Diameter Min. (Metric) 12.0 mm

Bundle Diameter Max. (Imperial) 8.0 "

Bundle Diameter Max. (Metric) 203.0 mm

Thickness T (Imperial) 0.0837 "

Cable Tie Head Length (Imperial) 0.88 "

Cable Tie Head Width (Imperial) 0.79 "

Thickness T (Metric) 2.2 mm

Logistics and Packaging

Quantity Per	bag
Package Quantity (Metric)	25
Carton Quantity	500
Weight (Metric)	18.6 kg

Material and Specifications

Material	Polyamide 6.6 (PA66)
Material Shortcut	PA66
Flammability	UL94 V2
Operating Temperature	-40°F to +185°F (-40°C to +85°C)
ROHS Compliant	Yes
Certification/Specification	UL
UL Listed (US and Canada)	No
UL Recognized (US and Canada)	Yes