

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)
[S2CM258HIRHSH1](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

HellermannTyton

S2CM258HIRHSH1



Article Number: 151-29400

Two Way Saddle Mount, Max Bundle Diameter 3.5", Stud Diameter 0.25", PA66HIRHS, Gray, 500/pkg



Download spec sheet

Base Data

Local Order Number S2CM258HIRHSH1

Type S2CM25

Color Gray (GY)

- Features and Benefits**
- Two way saddle separates bundles from wear and chafing.
 - Socket counterbore allows securing with a socket wrench from the top side for use with a weld stud or bolt.
 - Made from impact modified, heat stabilized, UV resistant material making it ideal for heavy duty applications.

Product Description HellermannTyton's saddle mount can be installed between two bundles (such as wires, cables, hoses, tubing, conduit, etc...) to separate them and prevent chafing and wear. Fastened to a frame rail or mounting bracket, this "H" profile on the saddle mount provides a tight circumferential loop on large and small bundles.

Fixation Method (FF) Screw Mounting and Rivet

Short Description Two Way Saddle Mount, Max Bundle Diameter 3.5", Stud Diameter 0.25", PA66HIRHS, Gray, 500/pkg

Product Dimensions

Length L (Imperial) 1.8 "

Length L (Metric) 45.0 mm

Width W (Imperial) 1.2 "

Width W (Metric) 30.0 mm

Cable Tie Width Max. (Imperial) 0.5 "

Cable Tie Width Max. (Metric) 12.5 mm

Height H (Imperial) 0.9 "

Height H (Metric) 23.0 mm

Height H2 (Imperial) 0.6 "

Height H2 (Metric) 15.0 mm

Bundle Diameter Max. (Imperial) 3.5 "

Bundle Diameter Max. (Metric) 89.0 mm

Mounting Hole Diameter D (Imperial) 0.24 "

Mounting Hole Diameter D (Metric) 6.0 mm

Stud Size (Imperial) 0.25 "

Stud Size (Metric) 6.35 mm

Logistics and Packaging

Quantity Per bag

Package Quantity (Metric) 500 Pieces

Material and Specifications

Material	Polyamide 6.6 high impact modified, heat stabilized, UV resistant (PA66HIRHS)
Material Shortcut	PA66HIRHS
Flammability	UL94 HB
Operating Temperature	-40°F to +230°F (-40°C to +110°C)
ROHS compliant (Article 4 - 1)	Yes