

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)
[SNP1GHS0M4](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

HellermannTyton

SNP1GHS0M4



Article Number: 190-00019

Snapper Hose Clamps, .237"/.263" Min/Max Diameter, PA66GF13%, Black, 1000/pkg



Download spec sheet

Base Data

Local Order Number SNP1GHS0M4

Type SNP1

Color Black (BK)

Features and Benefits

- Designed for quick, ratcheted installation and can be released and reused.
- Heat stabilized material is suitable for high temperature applications.

Product Description HellermannTyton snapper hose clamps are designed to provide a quick, ratcheted closure reducing installation time. The design also allows the clamp to be easily removed and re-applied when necessary. Snappers are made of high performing materials providing stability in a variety of diverse environments. Available in 32 standard sizes.

Short Description Snapper Hose Clamps, .237"/.263" Min/Max Diameter, PA66GF13%, Black, 1000/pkg

Product Dimensions

Fixation Method Plug-in mounting

Variant Closed

Width W2 (Imperial) 0.149 "

Width W2 (Metric) 3.78 mm

Bundle Diameter Min. (Imperial) 0.3 "

Bundle Diameter Min. (Metric) 6.0 mm

Bundle Diameter Max. (Imperial) 0.27 "

Bundle Diameter Max. (Metric) 6.8 mm

Diameter Min. (Imperial) 0.237 "

Diameter Min. (Metric) 6.02 mm

Diameter Max. (Imperial) 0.263 "

Diameter Max. (Metric) 6.68 mm

Wall Thickness WT (Imperial) 0.04 "

Wall Thickness WT (Metric) 1.01 mm

Logistics and Packaging

Quantity Per bag

Package Quantity (Metric) 1000

Carton Quantity 25000

Material and Specifications

Material Polyamide 6.6 glass filled impact modified heat stabilized (PA66GF13%)



Distributor of HellemanTyton: Excellent Integrated System Limited

Datasheet of SNP1GHS0M4 - SNPPR HOSE CLAMP MAX .262"

Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

Flammability UL94 HB

Operating Temperature -40°F to +221°F (-40°C to +105°C)

ROHS Compliant Yes