

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)
[SNP32GHS0K2](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

HellermannTyton

SNP32GHS0K2



Article Number: 192-10320

Snapper Hose Clamps, 1.23"/1.411" Min/Max Diameter, PA66GF13%, Black, 50/pkg



Download drawing



Download spec sheet

Base Data

Local Order Number SNP32GHS0K2

Type SNP32

Color Black (BK)

Features and Benefits

- Designed for quick, ratcheted installation and can be released and reused.
- Heat stabilized material is suitable for high temperature applications.

Product Description HellermannTyton snapper hose clamps are designed to provide a quick, ratcheted closure reducing installation time. The design also allows the clamp to be easily removed and re-applied when necessary. Snappers are made of high performing materials providing stability in a variety of diverse environments. Available in 32 standard sizes.

Short Description Snapper Hose Clamps, 1.23"/1.411" Min/Max Diameter, PA66GF13%, Black, 50/pkg

Product Dimensions

Fixation Method Plug-in mounting

Variant Closed

Width W2 (Imperial) 0.288 "

Width W2 (Metric) 7.32 mm

Bundle Diameter Min. (Metric) 31.2 mm

Bundle Diameter Max. (Imperial) 1.4 "

Bundle Diameter Max. (Metric) 35.8 mm

Diameter Min. (Imperial) 1.23 "

Diameter Min. (Metric) 31.24 mm

Diameter Max. (Imperial) 1.411 "

Diameter Max. (Metric) 35.84 mm

Nominal Diameter (Imperial) 1-5/16 "

Nominal Diameter (Metric) 33 mm

Wall Thickness WT (Imperial) 0.069 "

Wall Thickness WT (Metric) 1.8 mm

Logistics and Packaging

Quantity Per bag

Package Quantity (Metric) 50 Pieces

Carton Quantity 50 Pieces

Weight (Metric) 0.38 kg



Distributor of HellemanTyton: Excellent Integrated System Limited

Datasheet of SNP32GHS0K2 - SNPPR HOSE CLAMP MAX 1.436"

Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

Material Polyamide 6.6 glass filled impact modified heat stabilized (PA66GF13%)

Material Shortcut PA66GF13

Flammability UL94 HB

Operating Temperature -40°F to +221°F (-40°C to +105°C)

ROHS Compliant Yes