

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)
[SNP5010C2](#)

For any questions, you can email us directly:
sales@integrated-circuit.com

HellermannTyton

SNP5010C2



Article Number: 190-00248

Snapper Hose Clamps, 1.99"/2.323" Min/Max Diameter, POM, White, 100/pkg



Download drawing



Download spec sheet

Base Data

Local Order Number SNP5010C2

Type SNP50

Color White (WH)

Features and Benefits

- Designed for quick, ratcheted installation and can be released and reused.
- Polyacetal material resists chemicals, corrosion and UV rays making it suitable for extreme environments.

Product Description HellermannTyton snapper hose clamps are designed to provide a quick, ratcheted closure reducing installation time. The design also allows the clamp to be easily removed and re-applied when necessary. Snappers are made of high performing materials providing stability in a variety of diverse environments. Available in 32 standard sizes.

Short Description Snapper Hose Clamps, 1.99"/2.323" Min/Max Diameter, POM, White, 100/pkg

Product Dimensions

Fixation Method Plug-in mounting

Variant Closed

Width W2 (Imperial) 0.288 "

Width W2 (Metric) 7.32 mm

Bundle Diameter Min. (Imperial) 2.05 "

Bundle Diameter Min. (Metric) 52.0 mm

Bundle Diameter Max. (Imperial) 2.25 "

Bundle Diameter Max. (Metric) 57.5 mm

Diameter Min. (Imperial) 1.99 "

Diameter Min. (Metric) 50.55 mm

Diameter Max. (Imperial) 2.323 "

Diameter Max. (Metric) 59.0 mm

Wall Thickness WT (Imperial) 0.067 "

Wall Thickness WT (Metric) 1.7 mm

Logistics and Packaging

Quantity Per bag

Package Quantity (Metric) 100

Carton Quantity 600

Material and Specifications

Material Polyacetal (POM)



Distributor of HellemanTyton: Excellent Integrated System Limited

Datasheet of SNP5010C2 - SNPPR HOSE CLAMP MAX 2.277"

Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

Flammability UL94 HB

Operating Temperature -40°F to +185°F (-40°C to +85°C)

ROHS Compliant Yes