

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)
[T18R8-7K2](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

HellermannTyton

T18R8-7K2

Article Number: 111-01785

Standard Cable Tie, 4" Long, 18lb Tensile Strength, PA66, Gray/Purple Striped, 50/pkg



Download drawing



Download spec sheet

Base Data

Local Order Number T18R8-7K2

Type T18R

Color Gray (GY)
Purple (PE)

- Features and Benefits**
- Inside serrations allow for strong hold on cables and wire bundles.
 - Head design provides high tensile strength with very low insertion force.
 - Bent tail ensures a quick and simple installation.

Product Description HellermannTyton standard cable ties feature inside serrations providing a positive hold onto wire and cable bundles. The head design guarantees high tensile strength, as well as a low insertion force. The bent tail design allows quick and simple installations by hand. For high volume applications, tensioning tools are available to ensure consistent and safe installation.

Short Description Standard Cable Tie, 4" Long, 18lb Tensile Strength, PA66, Gray/Purple Striped, 50/pkg

Product Dimensions

Minimum Tensile Strength (Imperial) 18.0 lbs

Minimum Tensile Strength (Metric) 80.0 N

Length L (Imperial) 4.0 "

Length L (Metric) 100.0 mm

Fixation Method None

Identification Plate Position none

Releasable Closure No

Variant Inside Serrated

Width W (Imperial) 0.1 "

Width W (Metric) 2.45 mm

Bundle Diameter Min. (Imperial) 0.06 "

Bundle Diameter Min. (Metric) 1.5 mm

Bundle Diameter Max. (Imperial) 0.86 "

Bundle Diameter Max. (Metric) 22.0 mm

Logistics and Packaging

Quantity Per bag

Package Quantity (Metric) 50

Carton Quantity 10000



Material	Polyamide 6.6 (PA66)
Material Shortcut	PA66
Flammability	UL94 V2
Halogenfree	Yes
Operating Temperature	-40°F to +185°F (-40°C to +85°C)
ROHS Compliant	Yes
Certification/Specification	MIL 53421 UL-ZODZ2.E64139
UL Listed (US and Canada)	No
UL Recognized (US and Canada)	No