

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)
[T18RA5000](#)

For any questions, you can email us directly:
sales@integrated-circuit.com

HellermannTyton

T18RA5000

Article Number: 120-05004

Cable Tie for AT2000, 18 lb Tensile Strength, PA66, Natural, 5,000/reel



Download spec sheet

Base Data

Local Order Number T18RA5000

Type T18RA5000

Color Natural (NA)

Features and Benefits

- The AT2000 cable tie system is designed for automatic installation on bundles up to .75" and a minimum tensile strength of 18 lbs.
- Available in reels of 5,000 each or bandoliers of 50 each.

Product Description HellermannTyton offers the widest range of automatic cable tie tool systems which cover cable tie tensile strengths of 18, 30, and 50 pounds with bundle diameters between 1/16" to over 3". For use with HellermannTyton's Automatic Tool Systems.

Short Description Cable Tie for AT2000, 18 lb Tensile Strength, PA66, Natural, 5,000/reel

Product Dimensions

Minimum Tensile Strength (Imperial) 18.0 lbs

Minimum Tensile Strength (Metric) 80.0 N

Length L (Imperial) 4.0 "

Length L (Metric) 4.8 mm

Power Supply unit Electrical

Tie Closure plastic pawl

Width W (Imperial) 0.1 "

Width W (Metric) 2.5 mm

Bundle Diameter Min. (Imperial) 0.03 "

Bundle Diameter Min. (Metric) 0.7 mm

Bundle Diameter Max. (Imperial) 0.75 "

Bundle Diameter Max. (Metric) 20.0 mm

Logistics and Packaging

Quantity Per reel

Package Quantity (Metric) 5000

Carton Quantity 10000

Material and Specifications

Material Polyamide 6.6 (PA66)

Material Shortcut PA66

US MIL SPEC MS3367-4-9



Flammability UL94 V2

Operating Temperature -40°F to +185°F (-40°C to +85°C)

Certification/Specification SAE - AS33671
Cage Code 53421
UL-ZODZ2.E64139

UL Listed (US and Canada) No

UL Recognized (US and Canada) Yes