

## Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)  
[T30RA300HS](#)

For any questions, you can email us directly:

[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)

# HellermannTyton

## T30RA300HS



Article Number: 103-00003

Cable Tie for AT2060, 30 lb Tensile Strength, PA66HS, Black, 30/bandolier, 600/pkg



Download spec sheet

### Base Data

Local Order Number T30RA300HS

Type T30RA

Color Black (BK)

**Features and Benefits**

- The AT2060 cable tie system is designed for automatic installation on bundles up to 1.25" and a minimum tensile strength of 30 lbs.
- Available in reels of 3,000 each or bandoliers of 30 each.

**Product Description** HellermannTyton offers the widest range of automatic cable tie tool systems which cover cable tie tensile strengths of 18, 30, and 50 pounds with bundle diameters between 1/16" to over 3". For use with HellermannTyton's Automatic Tool Systems.

**Short Description** Cable Tie for AT2060, 30 lb Tensile Strength, PA66HS, Black, 30/bandolier, 600/pkg

### Product Dimensions

Minimum Tensile Strength (Imperial) 30.0 lbs

Minimum Tensile Strength (Metric) 135.0 N

Length L (Imperial) 6.0 "

Length L (Metric) 152.0 mm

Cycle Time 1.2 seconds

Identification Plate Position none

Reel Diameter (Metric) 450 mm

Reel Diameter (Imperial) 17.7 "

Reel Width (Metric) 182.8 m

Reel Width (Imperial) 7.197 "

Releasable Closure No

Voltage Range 27 Volt

Width W (Imperial) 0.14 "

Width W (Metric) 3.6 mm

Bundle Diameter Min. (Imperial) 0.06 "

Bundle Diameter Min. (Metric) 1.5 mm

Bundle Diameter Max. (Imperial) 1.25 "

Bundle Diameter Max. (Metric) 31.0 mm

Thickness T (Imperial) 0.05 "

Power Supply Electrical

Tension Force Adjustable

## Logistics and Packaging

---

|                                  |          |
|----------------------------------|----------|
| <b>Quantity Per</b>              | bag      |
| <b>Package Quantity (Metric)</b> | 600      |
| <b>Carton Quantity</b>           | 6000     |
| <b>Reel Weight (Imperial)</b>    | 7 lbs    |
| <b>Reel Weight (Metric)</b>      | 3.175 kg |
| <b>Weight (imperial)</b>         | 3.9 lbs  |

## Material and Specifications

---

|                                      |                                        |
|--------------------------------------|----------------------------------------|
| <b>Material</b>                      | Polyamide 6.6 heat stabilized (PA66HS) |
| <b>Material Shortcut</b>             | PA66HS                                 |
| <b>Flammability</b>                  | UL94 V2                                |
| <b>Operating Temperature</b>         | -40°F to +275°F (-40°C to +135°C)      |
| <b>UL Listed (US and Canada)</b>     | No                                     |
| <b>UL Recognized (US and Canada)</b> | Yes                                    |