Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

HellermannTyton
T3D02500M4

For any questions, you can email us directly:
sales@integrated-circuit.com

Distributor of HellermannTyton: Excellent Integrated System Limited
Datasheet of T3D02500M4 - T CLAMP-T3 SERIES .375"
Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

HellermannTyton

T3D02500M4

Article Number: 211-00134

P Clamp, .375" Width, .25" Max Bundle Dia, .203" Mounting Hole Dia, PA66, Black, 1000/pkg

RoHS

Download spec sheet

Base Data

Local Order Number	T3D02500M4
Type	T3D0250
Color	Black (BK)
Features and Benefits	• P-Clamps easily guide and locate wire and cables up to 0.625" in diameter. • Designed with a radiused edge to prevent chaffing and cutting into insulation.
Product Description	HellermannTyton P Clamps easily guide and locate wires and cables. The clamps are designed with a radiused edge to prevent chaffing and cutting into insulation. Available sizes up to 1" bundle diameters.
Short Description	P Clamp, .375" Width, .25" Max Bundle Dia, .203" Mounting Hole Dia, PA66, Black, 1000/pkg

Product Dimensions

Fixation Method	screw-hole
Variant	Closed
Width W (Imperial)	0.375 "
Width W (Metric)	9.53 mm
Bundle Diameter Max. (Imperial)	0.25 "
Bundle Diameter Max. (Metric)	6.35 mm
Mounting Hole Diameter D (Imperial)	0.203 "
Mounting Hole Diameter D (Metric)	5.1 mm
Wall Thickness WT (Imperial)	.050 "
Wall Thickness WT (Metric)	1.3 mm
Mounting Hole Centers (Imperial)	0.41 "
Mounting Hole Diameter D Max. (Metric)	5.1 mm
Mounting Hole Diameter D Min. (Metric)	5.1 mm

Logistics and Packaging

Quantity Per	bag
Package Quantity (Metric)	1000 Pieces
Carton Quantity	10000

Material and Specifications

Material	Polyamide 6.6 (PA66)
Material Shortcut	PA66
Flammability	UL94 V2

ROHS Compliant	Yes
UL Recognized (US and Canada)	Yes

© HellermannTyton 2015