

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)
[T50MI9C2](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

HellermannTyton

T50MI9C2



Article Number: 113-00032

Screw Mount Tie, 50lb, 12.4" Long, Max Bundle Diameter 3.4", #10 Screw, PA66, Natural, 100/pkg



Download spec sheet

Base Data

Local Order Number T50MI9C2

Type T50MI

Color Natural (NA)

Features and Benefits

- Mount design secures firmly with any #10 screw.
- Screw mount style creates low insertion and high extraction force.

Product Description Screw Mount Cable Ties are made of all plastic and provide a quick and simple method of mounting.

Short Description Screw Mount Tie, 50lb, 12.4" Long, Max Bundle Diameter 3.4", #10 Screw, PA66, Natural, 100/pkg

Product Dimensions

Minimum Tensile Strength (Imperial) 50.0 lbs

Minimum Tensile Strength (Metric) 225 N

Length L (Imperial) 12.4 "

Length L (Metric) 315.0 mm

Fixation Method fixing hole

Identification Plate Position none

Releasable Closure No

Tie Closure plastic pawl

Variant Inside Serrated

Width W (Imperial) 0.19 "

Width W (Metric) 4.7 mm

Height H (Imperial) 0.23 "

Height H (Metric) 5.7 mm

Bundle Diameter Min. (Imperial) 0.06 "

Bundle Diameter Min. (Metric) 1.5 mm

Bundle Diameter Max. (Imperial) 3.4 "

Bundle Diameter Max. (Metric) 85.0 mm

Mounting Hole Diameter D (Imperial) 0.22 "

Mounting Hole Diameter D (Metric) 5.5 mm

Mounting Hole Diameter D Max. 5.5 mm

(Metric) Mounting Hole Diameter D Min. (Metric) 5.5 mm

Logistics and Packaging



Package Quantity (Metric) 100

Carton Quantity 5000

Material and Specifications

Material Polyamide 6.6 (PA66)

Material Shortcut PA66

Flammability UL94 V2

Operating Temperature -40°F to +221°F (-40°C to +105°C)

ROHS Compliant Yes

UL Listed (US and Canada) No

UL Recognized (US and Canada) Yes