

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)
[T5D100010H4](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

HellermannTyton

T5D100010H4



Article Number: 211-00119

P Clamp, .5" Width, 1.0" Max Bundle Dia, .203" Mounting Hole Dia, PA66, White, 500/pkg



Download drawing



Download spec sheet

Base Data

Local Order Number T5D100010H4

Type T5D1000

Color White (WH)

Features and Benefits

- Easily guide and locate wire and cables up to 1.5" in diameter.
- Designed with a radiused edge to prevent chaffing and cutting into insulation.

Product Description HellermannTyton P Clamps easily guide and locate wires and cables. The clamps are designed with a radiused edge to prevent chaffing and cutting into insulation. Available sizes up to 1.5" bundle diameters.

Short Description P Clamp, .5" Width, 1.0" Max Bundle Dia, .203" Mounting Hole Dia, PA66, White, 500/pkg

Product Dimensions

Fixation Method screw-hole

Variant Closed

Width W (Imperial) 0.5 "

Width W (Metric) 12.7 mm

Bundle Diameter Max. (Imperial) 1.0 "

Bundle Diameter Max. (Metric) 25.4 mm

Mounting Hole Diameter D (Imperial) 0.203 "

Mounting Hole Diameter D (Metric) 5.1 mm

Wall Thickness WT (Imperial) .050 "

Wall Thickness WT (Metric) 1.3 mm

Mounting Hole Centers (Imperial) 0.91 "

Mounting Hole Diameter D Max. 5.1 mm

(Metric) Mounting Hole Diameter D Min. (Metric) 5.1 mm

Logistics and Packaging

Quantity Per bag

Package Quantity (Metric) 500 Pieces

Material and Specifications

Material Polyamide 6.6 (PA66)

Material Shortcut PA66

Flammability UL94 V2

Operating Temperature -40°F to +185°F (-40°C to +85°C)



Distributor of HellemannTyton: Excellent Integrated System Limited

Datasheet of T5D100010H4 - T CLAMP-T5 SERIES MAX DIA 1"

Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

UL Recognized (US and Canada) Yes

© HellemannTyton 2015