

## Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)  
[TAG1T1-100B](#)

For any questions, you can email us directly:

[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)

# HellermannTyton

## TAG1T1-100B

Article Number: 596-00005

Thermal Transfer Self-Laminating Label, 1.9" X .75" X 3.12", 2 Across, Vinyl, White, 2500/RL



Download drawing



Download spec sheet

### Base Data

**Local Order Number** TAG1T1-100B

**Type** TAG1T1

**Color** White (WH)

- Features and Benefits**
- HellermannTyton Self-Laminating Labels come on rolls on a standard 3" core for easy loading into a printer or caddy.
  - Labels are conformable so that they can bend around small gauge wires and tight bends without coming loose over time.
  - Labels are UL recognized for indoor and outdoor use to expand application options.
  - HellermannTyton thermal transfer labels work in any thermal transfer printer so that the use always has options to get labels printed without being locked into a single vendor.

**Color Marking Field** White (WH)

**Product Description** HellermannTyton thermal transfer self-laminating labels are a conformable vinyl film with a white printable surface followed by a clear tail that laminates the printed text when applied to a wire or cable. The labels are UL recognized for indoor and outdoor use with an aggressive acrylic adhesive that allows the label to bond to large and small diameter wires.

**Short Description** Thermal Transfer Self-Laminating Label, 1.9" X .75" X 3.12", 2 Across, Vinyl, White, 2500/RL

### Product Dimensions

**Length L (Imperial)** 3.12 "

**Length L (Metric)** 79.2 mm

**Width W (Imperial)** 1.9 "

**Width W (Metric)** 48.26 mm

**Height H (Imperial)** 3.12 "

**Height H (Metric)** 79.2 mm

**Height H2 (Imperial)** 3.12 "

**Height H2 (Metric)** 79.2 mm

**Height of printable area (imperial)** 0.75 "

**Height of printable area (metric)** 19.05 mm

**Bundle Diameter Min. (Imperial)** 0.334 "

**Bundle Diameter Min. (Metric)** 8.5 mm

**Bundle Diameter Max. (Imperial)** 0.716 "

**Bundle Diameter Max. (Metric)** 18.2 mm

**Horizontal Repeat HR (imperial)** 1.90 "

**Horizontal Repeat HR (metric)** 48.2 mm

**Print Method** Thermal Transfer

---

<b>Thickness T (Metric)</b>	25 µm
<b>Vertical Repeat VR (metric)</b>	86.8 mm
<b>Vertical Repeat VR (imperial)</b>	3.42 "
<b>Width of Liner WL (imperial)</b>	3.875 "
<b>Width of Liner WL (metric)</b>	98.42 mm

## Logistics and Packaging

---

<b>Quantity Per</b>	reel
<b>Package Quantity</b>	2500
<b>Package Quantity (Metric)</b>	2500
<b>Labels per Row</b>	2
<b>Weight (Metric)</b>	0.716 kg

## Material and Specifications

---

<b>Material</b>	Type 100B, Vinyl (PVC), white transparent (WH/CL), self laminating
<b>Material Shortcut</b>	100B
<b>Adhesive</b>	Acrylic
<b>Adhesive Shortcut</b>	Acrylic
<b>Adhesive Operating Temperature</b>	-40°F to +194°F (-40°C to +90°C)
<b>Operating Temperature</b>	-40°F to +194°F (-40°C to +90°C)
<b>ROHS Compliant</b>	Yes
<b>Certification/Specification</b>	UL-Recognized