

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)
[TAG21J-450](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

HellermannTyton

TAG21J-450

Article Number: 593-21450

Ink Jet Label, .5" X .75", 156 Per Sheet, 450 Material, White, 5000/pkg



Download spec sheet

Base Data

Local Order Number TAG21J-450

Type TAG21J

Color White (WH)

- Features and Benefits**
- HellermannTyton Ink Jet labels are sheet fed for easy loading and fast printing.
 - Ink Jet labels are made with high temperature materials and adhesives so that they will not be affected by the high heat of laser printing.
 - Ink Jet labels are printable using toner for long term UV exposure.
 - Ink Jet labels come in a variety of label sizes and types to fit most applications.

Product Description Ink Jet labels are durable, ink jet printable markers for applications requiring clear, crisp legibility. The labels are supplied on sheets and are printable using HellermannTyton Tagprint Pro software and a standard ink jet printer. Specially designed adhesives and topcoats accept the ink allowing for easy color printing for specific applications that require colors.

Short Description Ink Jet Label, .5" X .75", 156 Per Sheet, 450 Material, White, 5000/pkg

Product Dimensions

Length L (Imperial) 0.75 "

Length L (Metric) 19.05 mm

Width W (Imperial) 0.50 "

Width W (Metric) 12.7 mm

Height H (Imperial) 0.75 "

Height H (Metric) 19.05 mm

Horizontal Repeat HR (metric) 15.91 mm

Horizontal Repeat HR (imperial) 0.626 "

Print Method Inkjet

Vertical Repeat VR (imperial) 0.50 "

Vertical Repeat VR (metric) 12.70 mm

Logistics and Packaging

Quantity Per pack

Package Quantity (Metric) 5000

Carton Quantity 5000 Pieces

Labels per Column 12

Labels per Row 13

Labels per Sheet 156

Material and Specifications

Material	Type 450, Polyethylenterephthalat (PET)
Material Shortcut	450
Adhesive Shortcut	Acrylic
Adhesive	Acrylic
Adhesive Operating Temperature	-40°F to +302°F (-40°C to +150°C)
Operating Temperature	-40°F to +302°F (-40°C to +150°C)
ROHS Compliant	Yes