

## Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)  
[TAG2L-105](#)

For any questions, you can email us directly:

[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)

# HellermannTyton

## TAG2L-105

Article Number: 594-02105

Laser Tag Self-Laminating Label, .50" X .50" X 1.43", 112 Per Sheet, Polyester, White, 5000/pkg



Download drawing



Download spec sheet

### Base Data

Local Order Number TAG2L-105

Type TAG2L

Color White (WH)

- Features and Benefits**
- LaserTags are sheet fed for easy loading and fast printing.
  - LaserTags are made with high temperature materials and adhesives so that they will not be affected by the high heat of laser printing.
  - LaserTags are printable using toner for long term UV exposure.
  - LaserTags come in a variety of label sizes and types to fit most applications.

Color Marking Field White (WH)

**Product Description** LaserTags are durable, laser printable labels for applications requiring clear, crisp legibility. The labels are supplied on 8.5" X 11" sheets and are printable using HellermannTyton Tagprint Pro software and a standard laser printer. Specially designed adhesives and materials are used for the LaserTags, ensuring that the labels will not curl, change color, or jam standard laser printers.

**Short Description** Laser Tag Self-Laminating Label, .50" X .50" X 1.43", 112 Per Sheet, Polyester, White, 5000/pkg

### Product Dimensions

Length L (Imperial) 1.43 "

Length L (Metric) 36.4 mm

Width W (Imperial) 0.50 "

Width W (Metric) 12.7 mm

Height H (Imperial) 0.50 "

Height H (Metric) 12.7 mm

Height H2 (Imperial) 1.43 "

Height H2 (Metric) 36.5 mm

Height of printable area (imperial) 0.50 "

Height of printable area (metric) 12.70 mm

Bundle Diameter Min. (Imperial) 0.149 "

Bundle Diameter Min. (Metric) 3.80 mm

Bundle Diameter Max. (Imperial) 0.29 "

Bundle Diameter Max. (Metric) 7.60 mm

Outside Diameter Min. (Imperial) 0.29 "

Outside Diameter Min. (Metric) 3.8 mm

Outside Diameter Max. (Imperial) 0.149 "

Outside Diameter Max. (Metric) 7.60 mm

<b>Horizontal Repeat HR (metric)</b>	12.70 mm
<b>Print Method</b>	Laser
<b>Thickness T (Metric)</b>	35.0 µm
<b>Vertical Repeat VR (metric)</b>	36.40 mm
<b>Vertical Repeat VR (imperial)</b>	1.43 "
<b>Width of Liner WL (metric)</b>	215.00 mm
<b>Width of Liner WL (imperial)</b>	8.5 "

## Logistics and Packaging

---

<b>Quantity Per</b>	pack
<b>Package Quantity</b>	5000
<b>Package Quantity (Metric)</b>	5000
<b>Carton Quantity</b>	5000
<b>Labels per Column</b>	7
<b>Labels per Row</b>	16
<b>Labels per Sheet</b>	112
<b>Weight (Metric)</b>	0.113 kg

## Material and Specifications

---

<b>Material</b>	Type 105, Polyester (PET), white (WH)
<b>Material Shortcut</b>	105
<b>Adhesive</b>	Acrylic
<b>Adhesive Shortcut</b>	Acrylic
<b>Adhesive Operating Temperature</b>	-40°F to +302°F (-40°C to +150°C)
<b>Operating Temperature</b>	-40°F to +300°F (-40°C to +149°C)
<b>ROHS Compliant</b>	Yes