

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)
[TAG63L-105](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

HellermannTyton

TAG63L-105

Article Number: 594-63105

Laser Tag Self-Laminating Label, 1.0" X .5" X 1.33", 56 Per Sheet, Polyester, White, 2500/pkg



Download spec sheet

Base Data

Local Order Number TAG63L-105

Type TAG63L

Color White (WH)

- Features and Benefits**
- LaserTags are sheet fed for easy loading and fast printing.
 - LaserTags are made with high temperature materials and adhesives so that they will not be affected by the high heat of laser printing.
 - LaserTags are printable using toner for long term UV exposure.
 - LaserTags come in a variety of label sizes and types to fit most applications.

Color Marking Field White (WH)

Product Description LaserTags are durable, laser printable labels for applications requiring clear, crisp legibility. The labels are supplied on 8.5" X 11" sheets and are printable using HellermannTyton Tagprint Pro software and a standard laser printer. Specially designed adhesives and materials are used for the LaserTags, ensuring that the labels will not curl, change color, or jam standard laser printers.

Short Description Laser Tag Self-Laminating Label, 1.0" X .5" X 1.33", 56 Per Sheet, Polyester, White, 2500/pkg

Product Dimensions

Length L (Imperial) 1.33 "

Length L (Metric) 33.7 mm

Width W (Imperial) 1.0 "

Width W (Metric) 25.4 mm

Height H (Imperial) 0.75 "

Height H (Metric) 19.05 mm

Height H2 (Imperial) 1.33 "

Height H2 (Metric) 33.7 mm

Height of printable area (imperial) 0.35 "

Height of printable area (metric) 12.70 mm

Bundle Diameter Min. (Imperial) 0.15 "

Bundle Diameter Min. (Metric) 3.80 mm

Bundle Diameter Max. (Imperial) 0.29 "

Bundle Diameter Max. (Metric) 7.60 mm

Outside Diameter Min. (Imperial) 0.15 "

Outside Diameter Min. (Metric) 3.8 mm

Outside Diameter Max. (Imperial) 0.299 "

Outside Diameter Max. (Metric) 7.60 mm

Horizontal Repeat HR (imperial)	1.000 "
Print Method	Laser
Thickness T (Metric)	35.0 µm
Vertical Repeat VR (imperial)	1.33 "
Vertical Repeat VR (metric)	33.70 mm
Width of Liner WL (imperial)	8.5 "
Width of Liner WL (metric)	215.00 mm

Logistics and Packaging

Quantity Per	pack
Package Quantity	2500
Package Quantity (Metric)	2500
Carton Quantity	2500 Pieces
Labels per Column	7
Labels per Row	8
Labels per Sheet	56

Material and Specifications

Material	Type 105, Polyester (PET), white (WH)
Material Shortcut	105
Adhesive	Acrylic
Adhesive Shortcut	Acrylic
Adhesive Operating Temperature	-40°F to +302°F (-40°C to +150°C)
Operating Temperature	-40°F to +300°F (-40°C to +149°C)
ROHS Compliant	Yes