

## Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)  
[TAGH95-100](#)

For any questions, you can email us directly:

[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)

# HellermannTyton

## TAGH95-100

Article Number: 557-00028

Spirit Self-Laminating Printer Label, 1.5" X 1.0" X 3.75", Vinyl, White, 100/RL



Download spec sheet

### Base Data

**Local Order Number** TAGH95-100

**Type** TAGH95

**Color** White (WH)

**Features and Benefits**

- HellermannTyton 100 self-laminating vinyl utilizes an aggressive acrylic adhesive that allows the label to stay wrapped on wire gauges as small as .06" in diameter without starting to unwrap or flag.
- The label material is best printed with HellermannTyton HHHST series ribbons on the Spirit portable printing system for optimal print clarity.
- All Spirit self-laminating labels meet the requirements of UL-969 STANDARD FOR MARKING AND LABELING SYSTEMS edition - 4, under UL file number MH18396 to achieve long label life and print durability when used indoors or outdoors.

**Color Marking Field** White (WH)

**Product Description** The HellermannTyton Spirit printing system is easy to use and features a "What You See Is What You Get" (WYSIWYG) user interface that shows the outline of the label on the LCD screen for quick and easy editing and printing. The Spirit 2100 provides a fast, high quality, thermal transfer printing of labels that are designed to survive industrial environments. A wide variety of label materials, sizes and types are available to fit most applications.

**Mounting method Identification ETIM** Pasting / Stick

**Short Description** Spirit Self-Laminating Printer Label, 1.5" X 1.0" X 3.75", Vinyl, White, 100/RL

### Product Dimensions

**Length L (Imperial)** 1.0 "

**Length L (Metric)** 25.4 mm

**Variant** Roller form

**Width W (Imperial)** 1.5 "

**Width W (Metric)** 38.1 mm

**Height H (Imperial)** 1.0 "

**Height H (Metric)** 25.4 mm

**Height H2 (Imperial)** 3.75 "

**Height H2 (Metric)** 95.25 mm

**Bundle Diameter Min. (Imperial)** 0.389 "

**Bundle Diameter Min. (Metric)** 9.90 mm

**Bundle Diameter Max. (Imperial)** 0.86 "

**Bundle Diameter Max. (Metric)** 22.00 mm

**Print Method** Thermal Transfer

**Width of Liner WL (imperial)** 1.625 "

**Width of Liner WL (metric)** 41.25 mm

## Logistics and Packaging

---

<b>Quantity Per</b>	reel
<b>Package Quantity</b>	100
<b>Package Quantity (Metric)</b>	100
<b>Carton Quantity</b>	1 Reel
<b>Weight (Metric)</b>	0.3 kg

## Material and Specifications

---

<b>Material</b>	Type 100, Vinyl (PVC), white (WH), self laminating
<b>Material Shortcut</b>	100
<b>Adhesive</b>	Acrylic
<b>Adhesive Shortcut</b>	Acrylic
<b>Adhesive Operating Temperature</b>	-40°F to +194°F (-40°C to +90°C)
<b>Operating Temperature</b>	-40°F to +176°F (-40°C to +80°C)
<b>ROHS Compliant</b>	Yes
<b>Certification/Specification</b>	UL-Recognized