

## Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)  
[TAGPHONE](#)

For any questions, you can email us directly:

[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)

# HellermannTyton

## TAGPHONE

**Article Number:** 593-00001

**Ink Jet Label, 1.75" X .375", 84 Per Sheet, Paper, White, 1000/pkg**



Download spec sheet

### Base Data

**Local Order Number** TAGPHONE

**Type** TAGPHONE

**Color** White (WH)

- Features and Benefits**
- HellermannTyton Ink Jet labels are sheet fed for easy loading and fast printing.
  - Ink Jet labels are made with high temperature materials and adhesives so that they will not be affected by the high heat of laser printing.
  - Ink Jet labels are printable using toner for long term UV exposure.
  - Ink Jet labels come in a variety of label sizes and types to fit most applications.

**Product Description** Ink Jet labels are durable, ink jet printable markers for applications requiring clear, crisp legibility. The labels are supplied on sheets and are printable using HellermannTyton Tagprint Pro software and a standard ink jet printer. Specially designed adhesives and topcoats accept the ink allowing for easy color printing for specific applications that require colors.

**Short Description** Ink Jet Label, 1.75" X .375", 84 Per Sheet, Paper, White, 1000/pkg

### Product Dimensions

**Length L (Imperial)** 0.375 "

**Length L (Metric)** 9.52 mm

**Width W (Imperial)** 1.75 "

**Width W (Metric)** 44.45 mm

**Height H (Imperial)** 0.375 "

**Height H (Metric)** 9.52 mm

**Horizontal Repeat HR (imperial)** 1.750 "

**Horizontal Repeat HR (metric)** 44.45 mm

**Print Method** Laser

**Vertical Repeat VR (metric)** 9.52 mm

**Vertical Repeat VR (imperial)** 0.375 "

### Logistics and Packaging

**Quantity Per** pack

**Package Quantity** 1000

**Package Quantity (Metric)** 1000

**Carton Quantity** 1000

**Labels per Column** 21

**Labels per Row** 4



## Material and Specifications

---

<b>Material</b>	Paper (PAP)
<b>Material Shortcut</b>	PAP
<b>Adhesive Shortcut</b>	Acrylic
<b>Adhesive</b>	Acrylic
<b>Adhesive Operating Temperature</b>	-40°F to +302°F (-40°C to +150°C)
<b>Operating Temperature</b>	-40°F to +302°F (-40°C to +150°C)
<b>ROHS Compliant</b>	Yes