# Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

HellermannTyton
VWMDC4X5BK7

For any questions, you can email us directly:
sales@integrated-circuit.com

# HellermannTyton

## VWMDC4X5BK7

**Article Number: 854-09213**

**Vertical Wire Manager Dual-Sided, Center Mount, 4.0" x 5.0" Front, 83.0" Height, Black, 1/box**

Download drawing       Download spec sheet

## Base Data

| | |
|---|---|
| **Local Order Number** | VWMDC4X5BK7 |
| **Type** | VWMDC4X57 |
| **Color** | Black (BK) |
| **Features and Benefits** | • Can be mounted on the side of the relay rack as well as between two adjacent racks providing multiple placement options.<br>• Breakaway fingers can be removed to allow routing of large cable bundles.<br>• Features an easily removable plastic film on the cover which ensures a neat appearance and improves rack aesthetics when the wire managers are installed. |
| **Product Description** | The vertical wire managers are available in single and dual sided styles. They can be mounted on the side of the relay rack as well as between two adjacent racks. Equipped with feed-through holes to move cable from back to front and vice versa. |
| **Short Description** | Vertical Wire Manager Dual-Sided, Center Mount, 4.0" x 5.0" Front, 83.0" Height, Black, 1/box |

## Product Dimensions

| | |
|---|---|
| **Length L (Imperial)** | 83.0 " |
| **Length L (Metric)** | 2108.2 mm |
| **Height in Units** | 2U |
| **Width W (Imperial)** | 4.0 " |
| **Width W (Metric)** | 101.6 mm |
| **Width W2 (Imperial)** | 4.0 " |
| **Width W2 (Metric)** | 101.6 mm |
| **Height H (Imperial)** | 83.0 " |
| **Height H (Metric)** | 2108.2 mm |
| **Depth D (metric)** | 127.0 mm |
| **Depth D (imperial)** | 5.0 " |
| **Depth D2 (imperial)** | 5.0 " |
| **Depth D2 (metric)** | 127.0 mm |

## Logistics and Packaging

| | |
|---|---|
| **Quantity Per** | box |
| **Package Quantity** | 1 |
| **Package Quantity (Metric)** | 1 |
| **Carton Quantity** | 1 |

**Material and Specifications**