

# **Excellent Integrated System Limited**

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

Tripp Lite 0SU70028

For any questions, you can email us directly: <u>sales@integrated-circuit.com</u>



Distributor of Tripp Lite: Excellent Integrated System Limited Datasheet of 0SU70028 - MINICOM PX USB 1-PORT REMOTE



# **Tripp Lite**

1111 W. 35th Street Chicago, IL 60609 USA Telephone: 773.869.1234 www.tripplite.com

# PX USB Remote KVM Access

# MODEL NUMBER: 0SU70028





# Description

Complete access to your computer - any time, anywhere

PX USB is a high performance KVM IP Gateway providing complete BIOS level remote kvm access and control of your computer or server, from any location. PX USB comes with 256 AES security as standard, and is equally adept in small business environments, remote support applications, and Enterprise data centers. Whatever your circumstance, wherever your computer, PX USB gives you the confidence of complete access and control, always.

### Virtual Media capability for each server

The PX USB features virtual media technology allowing a remote user to effortlessly move files from his USB or CD-ROM drive to target servers that may be anywhere in the world. With PX USB you no longer have to be physically present at each server in order to install or recover software applications and install OS patches.

#### Complete remote support for mission critical applications

PX USB is an indispensable tool for remotely supporting mission-critical computers and devices. PX USB lets you instantly access the remote computer's BIOS, and accurately diagnose and even fix system faults - saving you the time and cost of a field technician roll out.

#### Scalable centralized management

The single-port PX USB handily solves the problem of blocked server access in the data center. With a number of PX USB devices connected, multiple remote users can control multiple servers, all at the same time. Additional PX USB devices can be added as your data center grows. PX USB is ideal for corporations operating servers at multiple sites such as testing labs, university campuses, branch offices, and multi-floor facilities. The rack-mountable PX USB also uses Power over Ethernet (PoE) technology for efficient, clutter free power management.

# Highlights

- Single port, palm-sized device
- Virtual Media for complete
  remote management
- Absolute Mouse Support for reduced installation hassle
- BIOS level access over IP connection
- Cost-effective & easily scalable
- Power over Ethernet & external
  power option
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

# System Requirements Operating System

 Compatible with Windows 98 and higher, Novell, Linux, SUN Solaris and Mac

#### Resolution

- Host Computer: Supports video resolutions up to 1600 x 1200 @ 85Hz
- Client Computer: Recommended
  client computer resolution should be higher than resolution on the host computer

#### **Package Includes**

- PX USB
- USB Cable Kit
- Rackmount Hardware
- Owner's Manual





# Tripp Lite

1111 W. 35th Street Chicago, IL 60609 USA Telephone: 773.869.1234 www.tripplite.com

### Features

- Single port, palm-sized device
- Virtual Media for complete remote management
- Absolute Mouse Support for reduced installation hassle
- BIOS level access over IP connection
- Management system enabled
- Cost-effective & easily scalable
- Ideal for isolated/widely distributed servers
- Power over Ethernet & external power option
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

# **Specifications**

| OVERVIEW                            |                                |
|-------------------------------------|--------------------------------|
| Users                               | 1                              |
| Accessories Type                    | Remote Management              |
| ENVIRONMENTAL                       |                                |
| Storage Temperature Range           | -40°C to 70°C / -40°F to 158°F |
| Relative Humidity                   | 80% Non-Condensing             |
| Operating Temperature               | 0°C to 40°C / 32°F to 104°F    |
| CONNECTIONS                         |                                |
| PC/Server Connections               | VGA; USB; PS/2                 |
| WARRANTY                            |                                |
| Product Warranty Period (Worldwide) | 3-year limited warranty        |

© 2016 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: http://www.tripplite.com/products/product-certification-agencies