

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Tripp Lite](#)
[TLP82NSATF](#)

For any questions, you can email us directly:

sales@integrated-circuit.com



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

Protect It! 230V Surge Protector with 8 French/Belgian Outlets, French Plug, 2280 Joules, Tel/Coax Protection

MODEL NUMBER: TLP82NSATF



Highlights

- 8 safety outlets
- 2 m cord
- Network protection
- 1 Line coax protection
- Protected/Grounded LED's
- 2280 joule rating

Package Includes

- TLP82NSATF surge suppressor
- 1.8 aerial cable and 2 aerial adapters
- 1.8 m gold coax cable
- 1.8 m network cable
- Instruction manual and warranty information

Description

Tripp Lite's Protect It!™ TLP82NSATF offers economical AC surge suppression for full protection of 220-250V home computers, printers, scanners, and desk lamps. The TLP82NSATF offers 8 French Type E outlets and a 2 meter AC line cord. Internal safety covers protect against accidental contact with unused outlets.

Features

- Protect It!™ TLP82NSATF offers economical AC surge suppression
- 2280 joules AC surge suppression shields equipment from surges and line noise
- 8 French Type E outlets protects computers and peripherals
- 2 m cord with French plug
- Lighted ON/OFF switch with circuit breaker
- Protected/Grounded LED's
- Network Protection
- Coax Protection
- Aerial Adapters
- Internal safety covers protect against accidental contact with unused outlets

Specifications

OUTPUT	
Output Receptacles	(8) French/Belgian
Output (Watts)	2500
Circuit Breaker (amps)	10



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

Transformer Accommodation	5
INPUT	
Nominal Input Voltage(s) Supported	230V AC
Recommended Electrical Service	230V (220-250V)
Maximum Input Amps	10
Input Connection Type	French
Input Cord Length (ft.)	6
Input Cord Length (m)	2
Voltage Compatibility (VAC)	220-250
Right-Angle Plug	Yes
USER INTERFACE, ALERTS & CONTROLS	
Diagnostic LED Details	Protected and Grounded
SURGE / NOISE SUPPRESSION	
AC Suppression Joule Rating	2280
DATALINE SURGE SUPPRESSION	
Telephone/DSL Protection	Yes
Cable (Coax) Protection	Yes
Cable (Coax) Protection Details	1 line
Network (Ethernet) Protection	Yes
Network (Ethernet) Protection Details	1 line
PHYSICAL	
Shipping Dimensions (hwd / in.)	14.80 x 7.80 x 2.18
Shipping Dimensions (hwd / cm)	37.59 x 19.81 x 5.54
Shipping Weight (lbs.)	2.50
Shipping Weight (kg)	1.13
Unit Dimensions (hwd / in.)	12.44 x 4.61 x 1.93
Unit Dimensions (hwd / cm)	31.60 x 11.71 x 4.90
Unit Weight (lbs.)	2.3
Unit Weight (kg)	1.04
Housing Color	Black
Receptacle Color	Black



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

Color (AC Line Cord)	Black
WARRANTY	
Product Warranty Period (Worldwide)	Lifetime limited warranty

© 2016 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice.

Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies:

<http://www.tripplite.com/products/product-certification-agencies>