

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Phoenix Contact](#)
[1595176](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

<https://www.phoenixcontact.com/us/products/1595176>



Device connector, rear mounting - RC-09P1N12H000 - 1595176

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

Device connector for rear wall, straight, shielded: Yes, Screw locking, M23, Number of positions: 8+1, Type of contact: Male connector, Solder connection, Axial O-ring, Central fastening M25 x 1.5, Panel thickness max.: 6.5 mm



Key commercial data

Packing unit	1 pc
Custom tariff number	85366990
Country of origin	Germany

Technical data

Product type	Circular connectors (device side)
Number of positions	9
Coding	N
Type	Device connector for rear wall
Mounting type	Central fastening M25 x 1.5
Rated current (IEC)	20
Rated voltage (IEC)	300
Thread	M23
Shielding	Yes
Signal type	Signal

Classifications

eCl@ss

eCl@ss 4.0	272607xx
eCl@ss 4.1	27260701
eCl@ss 5.0	27260701
eCl@ss 5.1	27260701
eCl@ss 6.0	27260708
eCl@ss 7.0	27440312
eCl@ss 8.0	27440103

<https://www.phoenixcontact.com/us/products/1595176>



Device connector, rear mounting - RC-09P1N12H000 - 1595176

Classifications

ETIM


ETIM 3.0	EC001121
ETIM 4.0	EC001121
ETIM 5.0	EC001121

UNSPSC

UNSPSC 6.01	43172015
UNSPSC 7.0901	43201404
UNSPSC 11	43172015
UNSPSC 12.01	43201404
UNSPSC 13.2	43201404

Drawings

Schematic diagram



Dimensioned drawing

